

TD 441-11Y



- 2 Contacts
- Metal enclosure
- Protection class IP65
- 2 cable entries M 20 x 1.5
- Lever can be transposed by 180°
- 106 mm x 99 mm x 63 mm (basic component)
- Continuous adjustment of lever position 360°
- Actuator head can be repositioned in steps 4 x 90°
- In temperature-resistant version, the roller can be mounted in two different positions on the shaft

Data

Ordering data

	TD 441-11Y
	101170463
EAN (European Article Number)	4030661297743
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

CCC
EAC

General data

Product name	441 roller lever D
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic

Gross weight	1,675 g
--------------	---------

General data - Features

Number of openers	1
Number of shutters	1

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 6 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection
	1.5 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	237 mm
Length of sensor	63 mm
Width of sensor	106 mm
Width of Castor	9 mm
Diameter of Castor	36 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	16 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	4 A
Switching element	NO contact, NC contact
Note (Switching element)	with double break
Switching principle	Creep circuit element

Ordering code

Product type description:

(1)(2) 441-11Y(3)-(4)-(5)

(1)

T Slow action (not available for AF/S)

M Snap action

(2)

S Plunger S

2S Telescopic plunger 2S

R Roller plunger R

K Offset roller lever K

J Offset roller lever J

2C Fork lever 2C

L Roller lever L

D Roller lever D

MAF/S Level switch AF/S

(3)

UE Slow action with overlapping contacts

(4)

without Cast iron enclosure

A Aluminium enclosure

(5)

T temperature-resistant and tropical version with ceramic insulation for -40 °C ... +200 °C

1276-2 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: kt441f09


| 96,8 kB | .png | 74.083 x 155.575 mm - 210 x 441

Pixel - 72 dpi

| 577,5 kB | .jpg | 201.083 x 422.628 mm - 570 x 1198

Pixel - 72 dpi

Dimension/Product/Basic



ID: 1t441g01

| 3,9 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel

- 72 dpi

| 29,6 kB | .cdr |

| 86,4 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

Diagramm/Product/Travel



ID: kt441s06

| 1,0 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel

- 72 dpi

| 55,1 kB | .jpg | 352.778 x 159.456 mm - 1000 x 452

Pixel - 72 dpi

Illustration/Product/Function



ID: 235hz05

| 15,2 kB | .cdr |

| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124

Pixel - 72 dpi

| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446

Pixel - 72 dpi

Dimension/Product/Actuator

