

BNS 300-01ZG-2230



- Ø M30
- Long life
- no mechanical wear
- Insensitive to soiling
- Thermoplastic enclosure
- With integral evaluation
- supplementary signalling output
- Insensitive to transverse misalignment
- Suitable for food processing industry only in combination with BPS 303

Data

Ordering data

	BNS 300-01ZG-2230
	101134031
EAN (European Article Number)	4030661279862
eCl@ss number, Version 9.0	27-27-24-02

Approval - Standards

EAC

General data

	BNS 300
	IEC 60947-5-3
	BG-GS-ET-14
Installation conditions (mechanical)	quasi-flush
Enclosure material	Glass-fibre, reinforced thermoplastic
Material of the nuts	Thermoplastic
Gross weight	130 g

General data - Features

Coding	Yes
Integral System Diagnostics, status	Yes
Safety monitoring module integrated	Yes
Number of openers	1
Number of safety contacts	1

Number of cable wires	4
-----------------------	---

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Magnet
Ensured switch distance "ON" S_{ao}	5 mm
Ensured switch distance "OFF" S_{ar}	15 mm
Direction of motion	Head-on to the active surface
Tightening torque of nuts, maximum	3 Nm

Mechanical data - Connection technique

Terminal Connector	Cable
Length of cable	1 m
Wire cross-section	0.8 mm ²
Wire cross-section	18 AWG
	PVC

Mechanical data - Dimensions

	M30
width across flats	36 BK
Length of sensor	78 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+55 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm 30 g / 11 ms

Electrical data

Voltage type	DC (direct current)
Switching voltage, maximum	250 VAC
Switching current, maximum	3 A

Switching capacity, maximum	750 W
Switching frequency, maximum	5 Hz

Electrical data - Relay outputs

Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0 A

Status indication

Note (Integral System Diagnostics, status)	The LED is illuminated when the guard is closed.
---	--

Scope of delivery

Included in delivery	Actuators must be ordered separately.
Delivery scope of Mounting material	2x nuts M30 x 1.5

Accessory

BPS 300
 BPS 303
 BPS 303 SS
 SRB-E-301ST
 SRB-E-201LC

Notes

Note (General)	Contact symbols shown for the closed condition of the guard device.
----------------	---

Ordering code

Product type description:

BNS 300-01ZG-(1)-(2)

(1)

without with cable

ST M12 connector

(2)

2211 higher switching distance

2230 supplementary signalling output

2246 Ue 42 VAC

Pictures

Photo/Product/Catalogue

ID: kbns3f04




| 225,4 kB | .jpg | 352.778 x 128.058 mm - 1000 x 363 Pixel - 72 dpi

| 15,4 kB | .png | 74.083 x 26.811 mm - 210 x 76 Pixel - 72 dpi

Dimension/Product/Basic

ID: 1bns3g01




| 3,0 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi

| 57,6 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697 Pixel - 72 dpi

| 30,4 kB | .cdr |

Graphic/Product/Contact




ID: kbns3k20

| 16,3 kB | .cdr |

| 51,3 kB | .jpg | 352.778 x 107.597 mm - 1000 x 305 Pixel - 72 dpi

Diagramm/Product/Curve

ID: kbns3a03



| 152,0 kB | .jpg | 352.778 x 200.378 mm - 1000 x 568 Pixel - 72 dpi

| 18,2 kB | .png | 74.083 x 41.981 mm - 210 x 119 Pixel - 72 dpi

| 119,1 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 062021-01-31T06:49:06+01:000601Europe/BerlinSun, 31 Jan 2021 06:49:06

+010006amSunday.31am31Europe/BerlinCET4901Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:49:06

+010001am31