

AZM 415-11/11ZPKF 24 VAC/DC



- Long life
- Robust design
- Manual release
- Metal enclosure
- Ex version available
- Cut clamp termination
- 141 mm x 100 mm x 56,5 mm
- 2 cable entries M 20 x 1.5
- 2 switches in one enclosure
- Adjustable ball latch to 400 N
- Interlock with protection against incorrect locking.
- Problem-free opening of stressed doors by means of bell-crank system

Data

Ordering data

	AZM 415-11/11ZPKF 24 VAC/DC
	101167209
EAN (European Article Number)	4030661218236
eCl@ss number, Version 9.0	27-27-26-03

Approval - Standards

cULus
CCC
EAC

General data

	AZM 415
	EN 60947-5-1
	BG-GS-ET-19
Active principle	electromechanical
Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	920 g

General data - Features

Power to unlock	Yes
Manual release	Yes
Number of actuating directions	1
Number of auxiliary contacts	2
Number of safety contacts	2
Number of guard doors	1

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Clamping force in accordance with ISO14119 F_{zh}	3,500 N
Latching force, minimum	150 N
Latching force, maximum	400 N
positive break travel	5 mm
Positive break force, minimum	15 N
Actuating speed, maximum	0.2 m/s

Mechanical data - Connection technique

Terminal Connector	Screw connection 2 x 0.75 mm ² 2 x 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	100 mm
Length of sensor	56.5 mm
Width of sensor	141 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+50 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage 4 kV

Electrical data

Thermal test current 6 A
Rated control voltage 24 VAC/DC
Utilisation category AC-15 230 VAC
Utilisation category AC-15 4 A
Utilisation category DC-13 24 VDC
Utilisation category DC-13 1 A
Electrical power consumption, maximum 10 W
Switching element NO contact, NC contact
Switching principle Creep circuit element

Other data

Note (applications) sliding safety guard
hinged safety guard

Notes

secured with locking screw
For manual release using M5 triangular key, available as accessory
Note (Manual release) Only used on units with power to unlock principle
Manual release can be carried out using a M5 triangular key.
A chain secures the sealing plug against loss (Protection class IP67)

Ordering code

Product type description:

AZM 415-(1)(2)PK(3)-(4) (5)(6)-(7)

(1)

11/11 2 NC contacts/2 NO contacts
11/02 3 NC contacts / 1 NO contacts
11/20 1 NC contacts / 3 NO contacts
02/11 3 NC contacts / 1 NO contacts
02/20 2 NC contacts / 2 NO contacts
02/02 4 NC contact

(2)

X Protection class IP54

Z Protection class IP67

(3)

without Power to unlock

A Power to lock

(4)

STR Connector M23 right

ST Connector M23 bottom

(5)

without Without manual release

E Manual release using triangular key

F with triangular key (secured with locking screw)

FE using triangular key

RS Manual release using key

T Emergency exit using latched pushbutton (power to unlock only)

TE Emergency exit using latched pushbutton and manual release, mounting outside (power to unlock only)

TEI Emergency exit using latched pushbutton and manual release, mounting inside (power to unlock only)

NS Emergency release using lock button

(6)

24VAC/DC Us: 24 VAC/DC

110VAC Us: 110 VAC

230VAC Us: 230 VAC

(7)

1637 Gold-plated contacts

(1)

A Power to lock

(2)

ST Connector M23 right

without Power to unlock

STR Connector M23 bottom

(3)

without Without manual release

E Manual release using triangular key (only for power to unlock principle)

(4)

1637 Gold-plated contacts

Photo/Product/Catalogue

SCHMERSAL
Lebensschutz

AZM 415-11/11gpld
 24 VACDC

IEC 60947-2-1 2P RT
 U_e 250V
 I_{nom} 8A
 P_{max} 2000 W
 AC-B3

230V


CE

UL

1m


| 618,6 kB | .jpg | 352.778 x 294.569 mm - 1000 x 835
Pixel - 72 dpi
| 41,7 kB | .png | 74.083 x 61.736 mm - 210 x 175
Pixel - 72 dpi

ID: 1azm4g01




| 9,5 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi
| 132,1 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695
Pixel - 72 dpi
| 35,2 kB | .cdr |

ID: 1azm4g11



| 6,8 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi
| 73,7 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701
Pixel - 72 dpi
| 44,0 kB | .cdr |

ID: kazm4k25



| 80,4 kB | .jpg | 352.778 x 188.031 mm - 1000 x 533
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 492021-01-30T21:17:49+01:000901Europe/BerlinSat, 30 Jan 2021 21:17:49

+010049pmSaturday.30pm31Europe/BerlinCET1701Europe/BerlinJanuary2021Sat, 30 Jan 2021 21:17:49
+010001pm31