



TA 471-02/02Y

- Metal enclosure
- 4 or 6 Contacts
- 3 cable entries M 25 x 1.5
- 194 mm x 123 mm x 130 mm (basic component)
- Continuous adjustment of lever position 360°

Data

Ordering data

	TA 471-02/02Y
	101061079
EAN (European Article Number)	4030661058030
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

cULus
CCC
EAC

General data

Product name	471 roller lever A
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	4,405 g

General data - Features

Number of NC, left	2
--------------------	---

Number of NC, right	2
---------------------	---

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	1,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 4 mm
Actuation direction	Each time 75° right-hand side and left-hand side rotation
Actuating speed, minimum	0.1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 1.5 mm ² 4 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	11 AWG

Mechanical data - Dimensions

Height of sensor	143 mm
Length of sensor	190 mm
Width of sensor	194 mm
Width of Castor	9 mm
Diameter of Castor	36 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	25 A
----------------------	------

Utilisation category AC-15	230 VAC
Utilisation category AC-15	10 A
Switching element	Opener (NC)
Note (Switching element)	with double break
Switching principle	Creep circuit element
Switching frequency	1,000 /h

Pictures

Photo/Product/Catalogue



ID: ktm-af01

| 44,3 kB | .png | 74.083 x 128.058 mm - 210 x 363
Pixel - 72 dpi

| 463,2 kB | .jpg | 352.778 x 609.953 mm - 1000 x 1729
Pixel - 72 dpi

Photo/Product/Catalogue




ID: kt-47f02

| 23,3 kB | .png | 74.083 x 65.969 mm - 210 x 187
Pixel - 72 dpi

| 278,1 kB | .jpg | 352.778 x 313.619 mm - 1000 x 889
Pixel - 72 dpi

Dimension/Product/Basic




ID: 1t-47g02

| 10,6 kB | .png | 74.083 x 51.506 mm - 210 x 146
Pixel - 72 dpi

| 118,6 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi

| 41,3 kB | .cdr |

Dimension/Product/Actuator



ID: 1tm-ab01

| 9,9 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 104,6 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693
Pixel - 72 dpi

Illustration/Product/Function



ID: 235hz05

| 15,2 kB | .cdr |

| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124
Pixel - 72 dpi

| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 572021-01-31T16:16:57+01:000401Europe/BerlinSun, 31 Jan 2021 16:16:57

+010057pmSunday.31pm31Europe/BerlinCET1601Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:16:57

+010001pm31