


**NDTGR/BL**

## Data

### Ordering data

|                               |               |
|-------------------------------|---------------|
|                               | NDTGR/BL      |
|                               | 101163565     |
| EAN (European Article Number) | 4030661484594 |
| eCl@ss number, Version 9.0    | 27-37-12-10   |

### Approval - Standards

cULus  
IPA

### General data

|                                 |                                          |
|---------------------------------|------------------------------------------|
| Product name                    | NDT - Pushbutton                         |
|                                 | EN 60947-5-1                             |
|                                 | IEC/EN 60947-1                           |
| Versions                        | Embeddable button - Front plate mounting |
| Design                          | Round                                    |
| Sealing type                    | Membrane<br>Lip gaskets                  |
| Material of the operators       | ABS                                      |
| Material of the front ring      | ABS, chrome-plated                       |
| Colour of the operating element | Blue                                     |
| Colour of the front ring        | Silver                                   |
| Colour of the bellows           | Black                                    |
| Gross weight                    | 25 g                                     |

### General data - Features

|                 |     |
|-----------------|-----|
| Mounting flange | Yes |
|-----------------|-----|

Probing possible Yes

Fully insulated Yes

#### Mechanical data

Unlocking without  
Mounting Mounting flange EFM  
Actuating stroke 5 mm  
Tightening torque of the screw 0.6 Nm

#### Mechanical data - Dimensions

Height 11 mm  
diameters for the actuating heads 44.5 mm  
Diameter hole 22.3 mm  
Diameter hole, with tolerance indication 22.3 + 0.4 mm  
Thickness, of the front panel, minimum 1.5 mm  
Thickness of the front panel, maximum 6 mm  
Spacing 50 x 50 mm

#### Ambient conditions

IP67  
IP69K  
Ambient temperature, minimum -25 °C  
Ambient temperature, maximum +80 °C

#### Ordering code

Product type description:

-

|                        |                                                                                                        |
|------------------------|--------------------------------------------------------------------------------------------------------|
| <b>(1)DT(8)(2)</b>     | Pushbutton                                                                                             |
| <b>(1)DM(2)</b>        | Pushbutton with diaphragm for dust protection                                                          |
| <b>(1)DL(8)(2)</b>     | Illuminated pushbutton                                                                                 |
| <b>(1)DLM(2)</b>       | Illuminated pushbutton with diaphragm for dust protection                                              |
| <b>(1)ML(2)</b>        | Indicator light with flat collar                                                                       |
| <b>(1)MLH(2)</b>       | Indicator light with high collar                                                                       |
| <b>(1)DP(3)(8)(2)</b>  | Mushroom head impact button without latching                                                           |
| <b>(1)DTP(3)(8)(2)</b> | Mushroom head impact button without latching (only N-programm)                                         |
| <b>(1)DLP(3)(8)(2)</b> | Mushroom head impact button illuminated, without latching (only N programme)                           |
| <b>(1)DRR(3)(8)(2)</b> | Mushroom head impact button with latching, unlock by turning and pulling (pulling only in N programme) |
| <b>(1)DRZ(3)(8)(2)</b> | Mushroom head impact button with latching, unlock by pulling                                           |
| <b>(1)WS21(4)(5)</b>   | Selector switch with 2 positions:                                                                      |
| <b>(1)WT21(4)(5)</b>   | Selector switch with 1 momentary position                                                              |

|                        |                                                                         |
|------------------------|-------------------------------------------------------------------------|
| <b>(1)WS32(4)(5)</b>   | Selector switch with 3 maintained positions                             |
| <b>(1)WT32(4)(5)</b>   | Wahlschalter mit 2 Taststellungen                                       |
| <b>(1)WST32(4)(5)</b>  | Selector switch: switching, latching                                    |
| <b>(1)WTS32(4)(5)</b>  | Selector switch: latching, switching                                    |
| <b>(1)SS21S(4)(5)</b>  | Key-operated selector switch with 2 maintained positions                |
| <b>(1)ST21S(4)(5)</b>  | Key-operated selector switch with 1 momentary position                  |
| <b>(1)SS32S(4)(5)</b>  | Key-operated selector switch with 3 maintained positions                |
| <b>(1)ST32S(4)(5)</b>  | Key-operated selector switch with 2 momentary positions, left and right |
| <b>(1)SST32S(4)(5)</b> | Key-operated selector switch: switching, latching                       |
| <b>(1)STS32S(4)(5)</b> | Key-operated selector switch: latching, switching                       |
| <b>NB, MBN, BN</b>     | <b>Blanking plug</b>                                                    |

(1)

- **Command and signalling devices:**

**E** "E" program

**N** "N" program

**R** "R" program

(2)

- **Colour of button surface:**

**SW** Black

**GB** Grey

(3)

- **Head diameter of mushroom head impact button 30 mm:**

**30** 30 mm

**35** 35 mm

**40** 40 mm

**42** 42 mm

**45** 45 mm

**50** 50 mm

**55** 55 mm

**70** 70 mm

(4)

- **Toggle length in mm:**

**without** Short toggle

**.1** Long toggle

(5)

- **Colour of toggle:**

**without** Grey

(6)

- **Key-withdrawal position (3 positions):**

**1** Position left

**2** Position middle

**3** Position right

(7)

- **Key-withdrawal position (2 positions):**

**1** Position left

**2** Position right

(8)

- **Colour of diaphragm (only N programme):**

**without** Black

## Pictures

### Photo/Product/Catalogue



ID: kndt-f07

| 37,2 kB | .png | 74.083 x 66.322 mm - 210 x 188

Pixel - 72 dpi

| 384,6 kB | .jpg | 352.778 x 316.794 mm - 1000 x 898

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 302021-01-31T13:12:30+01:000101Europe/BerlinSun, 31 Jan 2021 13:12:30

+010030pmSunday.31pm31Europe/BerlinCET1201Europe/BerlinJanuary2021Sun, 31 Jan 2021 13:12:30

+010001pm31