

CSS 11-30S-D-M-ST



- Ø M30
- Connector M12, 8-pole
- Stainless steel enclosure
- Max. length of the sensor chain 200 m
- Max. 31 sensors can be wired in series.
- 2 short-circuit proof PNP safety outputs
- High repeat accuracy of the switching points
- Safety sensor can also be installed behind V4A covers.
- Integral cross-short, wire-breakage and external voltage monitoring of the safety cables up to the control cabinet

Data

Ordering data

	CSS 11-30S-D-M-ST
	101204612
EAN (European Article Number)	4030661381664
eCl@ss number, Version 9.0	27-27-24-03

Approval - Standards

TÜV
cULus
EAC

General data

	CSS 30S
	IEC 61508
	IEC 60947-5-3
Active principle	inductive
Housing construction form	Cylinder, thread

Installation conditions (mechanical)	not flush
Sensor topology	Sensor for series wiring
Enclosure material	Stainless steel
Gross weight	245 g
Reaction time, maximum	60 ms
Duration of risk, maximum	60 ms

General data - Features

Diagnostic output	Yes
Short circuit detection	Yes
Short-circuit recognition	Yes
Safety functions	Yes
Cascadable	Yes
Integral System Diagnostics, status	Yes
Number of LEDs	2
Number of semi-conductor outputs with signaling function	1
Number of fail-safe digital outputs	2
Number of Series-wiring of sensors	31

Safety appraisal

	ISO 13849-1 IEC 60947-5-3 IEC 61508
Performance level, up to	e
Control category to EN13849	4
PFH-value	$3.60 \times 10^{-9} / \text{h}$
Safety Integrity Level (SIL), applicable for	3
Mission Time	20 Year(s)

Mechanical data

Actuating panels	Actuation from top
Active area	front side
Switch distance	11 mm
Ensured switch distance "ON" S_{ao}	8 mm
Ensured switch distance "OFF" S_{ar}	15 mm

Hysteresis (Switch distance), maximum	2 mm
Repeat accuracy R R	1 mm

Mechanical data - Connection technique

Note	The cable section of the interconnecting cable must be observed for both wiring variants! Cable length and cable section alter the voltage drop depending on the output current
------	---

Mechanical data - Dimensions

	M30
Length of sensor	99.5 mm

Ambient conditions

Protection class	IP 69 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+65 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm
	30 g / 11 ms
	II

Ambient conditions - Insulation value

Rated impulse withstand voltage	0.8 kV
	III
	3

Electrical data

Voltage type	DC (direct current)
No-load current	100 mA
Rated operating voltage, minimum	20.4 VDC
Rated operating voltage, maximum	26.4 VDC
Operating current	600 mA
Required rated short-circuit current to EN 60947-5-1	100 A

Switching frequency, approx. 3 Hz

Electrical data - Fail-safe digital outputs

Rated operating current (safety outputs)	250 mA
Output current, (fail-safe output), maximum	0.3 A
Versions	p-type
Voltage drop U_d , maximum	0.5 V
Current leakage	0.5 mA
Voltage, Utilisation category DC12	24 VDC
Current, Utilisation category DC12	0.3 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.3 A

Electrical data - Diagnostic output

Versions	p-type
Voltage drop U_d , maximum	5 V
Voltage, Utilisation category DC12	24 VDC
Current, Utilisation category DC12	0.1 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.1 A

Electrical data - Electromagnetic compatibility (EMC)

IEC 61000-6-4

IEC 61000-6-2

Pin assignment

PIN 1	1A1 Ue: (1)
PIN 2	X1 Safety input 1
PIN 3	A2 GND
PIN 4	Y1 Safety output 1
PIN 5	OUT Diagnostic output
PIN 6	X2 Safety input 2
PIN 7	Y2 Safety output 2
PIN 8	IN without function

Scope of delivery

Included in delivery	Actuators must be ordered separately.
Delivery scope of Mounting material	2x Mounting material M30 x 1.5 nuts

Accessory

CST 30S-1
PROTECT PSC1
SRB-E-301ST
SRB-E-201LC

Notes

Note (General)	Evaluation requirements: The switch-off pauses of 250 µs – 1500 µs must be tolerated by the evaluation. The switch-off time of the safety sensor of 250 µs is additionally extended according the cable length and the capacity of the cable used. Typically a switch off time of 500 µs with 100 m of connection cable is reached.
----------------	---

Ordering code

Product type description:

CSS 30S-(1)-M-ST

(1)

D With diagnostic output
SD Serial diagnostic output

Pictures


Photo/Product/Catalogue



ID: kcsc3f14

| 310,8 kB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 Pixel - 72 dpi
| 29,4 kB | .png | 74.083 x 111.125 mm - 210 x 315 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1css3g05

| 30,3 kB | .cdr |

| 3,7 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 84,4 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

Diagramm/Product/Curve




ID: kc333d03

| 75,4 kB | .jpg | 352.778 x 233.892 mm - 1000 x 663
Pixel - 72 dpi

| 3,4 kB | .png | 74.083 x 49.036 mm - 210 x 139 Pixel
- 72 dpi

| 21,1 kB | .cdr |

Illustration/Product/Function



ID: kc333a09

| 31,2 kB | .cdr |

| 3,6 kB | .png | 74.083 x 221.192 mm - 210 x 627
Pixel - 72 dpi

| 221,5 kB | .jpg | 352.778 x 1053.394 mm - 1000 x 2986 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 322021-01-31T06:05:32+01:00601Europe/BerlinSun, 31 Jan 2021 06:05:32

+010032amSunday.31am31Europe/BerlinCET0501Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:05:32

+010001am31