

# XCSLF3535333

metal safety switch XCSLF-2NC+4NO- slow  
break - 3 entries tapped 1/2" NPT - 120V



## Main

|                                                          |                                                                                                                                                                                          |
|----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product                                         | Preventa Safety detection                                                                                                                                                                |
| Product or component type                                | Safety switch                                                                                                                                                                            |
| Component name                                           | XCSLF                                                                                                                                                                                    |
| Design                                                   | Slim                                                                                                                                                                                     |
| Material                                                 | Metal                                                                                                                                                                                    |
| Head type                                                | Key operated turret head                                                                                                                                                                 |
| Contacts type and composition                            | 1 NC + 2 NO                                                                                                                                                                              |
| Contact operation                                        | Slow-break, break before make                                                                                                                                                            |
| Solenoid contacts type and composition                   | 1 NC + 2 NO (slow-break, break before make)                                                                                                                                              |
| Cable entry                                              | 3 entries tapped for 1/2" NPT                                                                                                                                                            |
| Electromagnet interlocking                               | Locking on de-energisation and unlocking on energisation of solenoid                                                                                                                     |
| [Us]&nbsp;solenoid&nbsp;rate&nbsp;of&nbsp;supply voltage | 120 V, 50/60 Hz                                                                                                                                                                          |
| Electrical connection                                    | Spring terminal, clamping capacity: 1 x 1.5 mm <sup>2</sup> flexible or solid cable<br>Spring terminal, clamping capacity: 2 x 0.5 mm <sup>2</sup> flexible cables with 13 mm bared ends |
| Number of poles                                          | 3                                                                                                                                                                                        |
| Locking options description                              | With interlocking, locking by solenoid                                                                                                                                                   |
| Local signalling                                         | 1 LED (orange) for actuator withdrawn<br>1 LED (green) for actuator inserted and locked                                                                                                  |
| Signalling circuit voltage                               | 120 V                                                                                                                                                                                    |

## Complementary

|                                              |                                                                                                                              |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Positive opening                             | With NC contact                                                                                                              |
| Supply voltage type                          | AC/DC                                                                                                                        |
| Supply frequency                             | 50/60 Hz                                                                                                                     |
| Load factor                                  | 1                                                                                                                            |
| Signalling circuit type                      | AC                                                                                                                           |
| Mechanical durability                        | 1000000 cycles                                                                                                               |
| Minimum actuation speed                      | 0.01 m/s                                                                                                                     |
| Maximum actuation speed                      | 0.5 m/s                                                                                                                      |
| [Ie] rated operational current               | 0.55 A at 24 V, DC-13, R300 conforming to EN/IEC 60947-5-1<br>0.75 A at 240 V, AC-15, C300 conforming to EN/IEC 60947-5-1    |
| [Ithe] conventional enclosed thermal current | 4 A                                                                                                                          |
| Maximum load current                         | <= 15 A                                                                                                                      |
| [Ui] rated insulation voltage                | 300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14<br>250 V (pollution degree 3) conforming to EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage       | 4 kV EN/IEC 60947-5-1                                                                                                        |
| Minimum switching current                    | 10 mA at 20 °C                                                                                                               |
| Minimum switching voltage                    | 17 V                                                                                                                         |
| Short-circuit protection                     | 4 A cartridge fuse type gG (gl)<br>6 A type fast blow                                                                        |
| Maximum actuator forcible withdrawal rtc     | 3000 N                                                                                                                       |

|                                       |                                                                                                                                                                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Minimum actuator force for extraction | 20 N                                                                                                                                                                                                                                                                   |
| Resistance to mechanical impact       | 9.6 J against the partition<br>6.4 J without partition                                                                                                                                                                                                                 |
| Maximum operating rate                | 10 cyc/mn for maximum durability                                                                                                                                                                                                                                       |
| Safety level                          | Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach SIL 3 conforming to EN/IEC 61508 |
| Safety reliability data               | B10d = 5500000 value given for a life time of 20 years limited by mechanical or contact wear                                                                                                                                                                           |
| Body material                         | Zamak                                                                                                                                                                                                                                                                  |
| Head material                         | Zamak                                                                                                                                                                                                                                                                  |
| Depth                                 | 51 mm                                                                                                                                                                                                                                                                  |
| Height                                | 205 mm                                                                                                                                                                                                                                                                 |
| Width                                 | 44 mm                                                                                                                                                                                                                                                                  |
| Net weight                            | 1.1 kg                                                                                                                                                                                                                                                                 |

## Environment

|                                       |                                                                                                                        |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| Standards                             | CSA C22.2 No 14<br>UL 508<br>EN 1088/ISO 14119<br>EN/IEC 60947-5-1<br>EN/IEC 62061<br>EN/ISO 13849-1<br>EN/IEC 60204-1 |
| Product certifications                | CSA<br>TÜV<br>UL                                                                                                       |
| Protective treatment                  | TC                                                                                                                     |
| Ambient air temperature for operation | -25...60 °C                                                                                                            |
| Ambient air temperature for storage   | -40...70 °C                                                                                                            |
| Vibration resistance                  | 5 gn (f= 10...500 Hz) conforming to IEC 60068-2-6                                                                      |
| Shock resistance                      | 10 gn for 11 ms conforming to IEC 60068-2-27                                                                           |
| Electrical shock protection class     | Class I conforming to EN/IEC 61140                                                                                     |
| IP degree of protection               | IP66 conforming to EN/IEC 60529 and EN/IEC 60947-5-1<br>IP67                                                           |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 1.167 kg |
| Package 1 Height | 0.570 dm |
| Package 1 width  | 0.730 dm |
| Package 1 Length | 2.280 dm |

## Offer Sustainability

|                            |                                                                                                |
|----------------------------|------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                          |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                              |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                            |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                  |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                        |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|