

EX-ZR 355-11Z-3G/D



- Metal enclosure
- 66,7 mm x 76 mm x 38 mm
- 3 cable entries M 20 x 1.5
- Mounting details to EN 50041
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°
- Including Ex-certified screwed cable gland and screw plug
- Snap action with constant contact pressure up to switching point

Data

Ordering data

	EX-ZR 355-11Z-3G/D
	101193310
EAN (European Article Number)	4030661355320
eCl@ss number, Version 9.0	27-27-26-01

Explosion protection

EN 60079-15
 EN 60079-31
 IEC 60079-0
 22
 2
 3D
 3G
 Ⓜ II 3G Ex nC IIC T5 Gc X
 Ⓜ II 3D Ex tc IIIC T90°C Dc X

Manufacturer declaration	ATEX Zone 2 and 22
--------------------------	--------------------

General data

Product name	EX-Z 355 roller plunger _R IEC 60947-5-1 BG-GS-ET-15
Housing construction form	Norm construction design C
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	287 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Roller plunger
Mechanical life, minimum	30,000,000 Operations
Impact energy, maximum	1 J
Actuating force, minimum	12 N
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note Bounce duration	Bounce duration in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	7 mm
Cable cross-section of the cable glands, maximum	12 mm
	0.75 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Wire cross-section	13 AWG
--------------------	--------

Mechanical data - Dimensions

Height of sensor	116.6 mm
Length of sensor	38 mm
Width of sensor	40.5 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Snap switch element
Switching frequency	5,000 /h
Switchover time, maximum	2 ms

Ordering code

Product type description:

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

7H-2138 Roller lever 7H for position switches with safety function

1K Offset roller lever 1K

3K Angle roller lever 3K

11	1 NO contacts/1 NC contact
02	2 NC contact
20	2 NO contacts (not suitable for safety applications)
01/01	1 NC contact left / 1 NC contact right
12	1 NO contact/2 NC contacts
03	3 NC contact

H Slow action with staggered contacts


UE Slow action with overlapping contacts

1297 Enclosure with transverse slotted holes

2138 Roller lever 7H for position switches with safety function

1637 Gold-plated contacts

Photo/Product/Catalogue



| 72,7 kB | .png | 74.083 x 119.239 mm - 210 x 338
Pixel - 72 dpi


| 622,7 kB | .jpg | 228.247 x 367.947 mm - 647 x 1043
Pixel - 72 dpi

Technical drawing of a 1000mm x 1000mm x 100mm plate. The drawing includes a top view and a side view. The top view shows a square plate with a central hole of diameter 100mm, four corner holes of diameter 20mm, and four side holes of diameter 20mm. The side view shows the plate's thickness of 100mm and the positions of the holes. Dimensions are given in millimeters (mm).

ID: k-355g01

| 133,4 kB | .jpg | 352.778 x 215.9 mm - 1000 x 612
Pixel - 72 dpi
| 30,4 kB | .cdr |
| 4,4 kB | .png | 74.083 x 45.156 mm - 210 x 128 Pixel
- 72 dpi


Diagramm/Product/Travel



ID: kr335s12

| 67,0 kB | .jpg | 352.778 x 188.031 mm - 1000 x 533
Pixel - 72 dpi
| 2,4 kB | .png | 74.083 x 39.511 mm - 210 x 112 Pixel
- 72 dpi
| 25,9 kB | .cdr |


Dimension/Product/Actuator



ID: 1r336g01

| 6,6 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi
| 66,1 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703
Pixel - 72 dpi
| 51,1 kB | .cdr |

Illustration/Product/Function



ID: 235rz01

| 149,7 kB | .jpg | 352.778 x 799.394 mm - 1000 x
2266 Pixel - 72 dpi
| 15,2 kB | .cdr |
| 2,9 kB | .png | 74.083 x 167.922 mm - 210 x 476
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 282021-01-31T17:47:28+01:000501Europe/BerlinSun, 31 Jan 2021 17:47:28

+010028pmSunday.31pm31Europe/BerlinCET4701Europe/BerlinJanuary2021Sun, 31 Jan 2021 17:47:28

+010001pm31