



Model Number

NMB6-F104M-E0-FE-200MM-V1

Features

- Sensing range 6 mm
- Ferrous targets
- Stainless steel sensing face
- 200 mm M12 male cordset with PUR jacket
- Power and output LEDs

Technical Data

General specifications

Switching function	Normally open (NO)
Output type	NPN
Rated operating distance	s_n 6 mm
Installation	flush
Assured operating distance	s_a 0 ... 4.86 mm
Actuating element	Ferrous targets
Reduction factor r_{Al}	0
Reduction factor r_{Cu}	0
Reduction factor r_{304}	0.6 ... 0.8
Reduction factor r_{Si37}	1
Output type	3-wire

Nominal ratings

Operating voltage	U_B	10 ... 30 V DC
Switching frequency	f	20 Hz
Hysteresis	H	5 ... 15 typ. 10 %
Reverse polarity protection		reverse polarity protected
Short-circuit protection		yes
Voltage drop	U_d	≤ 2 V
Operating current	I_L	≤ 100 mA
Current consumption		≤ 22 mA
Off-state current	I_r	≤ 10 μ A

Indicators/operating means

Operation indicator	Dual LED
	Green: power Yellow: output

Standard conformity

Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007
-----------	---

Ambient conditions

Ambient temperature	-25 ... 70 °C (-13 ... 158 °F)
---------------------	--------------------------------


Mechanical specifications

Connection type	Cable connector M12 x 1, 3-pin with PUR cable 200 mm
Core cross-section	0.34 mm ²
Housing material	Stainless steel 1.4305 / AISI 303
Degree of protection	IP67


Approvals and certificates

UL approval	cULus Listed, General Purpose
CCC approval	CCC approval / marking not required for products rated ≤ 36 V

Dimensions




Electrical Connection





Pinout



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)