





Inductive sensor NJ2-F-E02-2.062-V1

- 4-wire DC
- Weld Immune
- Sensing range 2 mm
- 1000 psi rating

Cylinder Position Switch



Dimensions



Technical Data

General specifications

Switching function		Normally open (NO)
Output type		PNP/NPN
Rated operating distance	s_n	2 mm
Installation		flush
Output polarity		DC
Assured operating distance	s_a	0 ... 1.62 mm
Reduction factor r_{AI}		0.4
Reduction factor r_{304}		0.85

Nominal ratings

Operating voltage	U_B	10 ... 30 V DC
Switching frequency	f	0 ... 30 Hz
Hysteresis	H	10 ... 20 typ. 15 %

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 904478_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS


Technical Data

Reverse polarity protection		yes
Short-circuit protection		yes
Voltage drop	U_d	$\leq 2 \text{ V DC}$
Operating current	I_L	$\leq 200 \text{ mA}$
Off-state current	I_r	$\leq 100 \mu\text{A}$
No-load supply current	I_0	$\leq 35 \text{ mA}$
Mag. Field strength, AC fields		250 mT
Mag. Field strength, DC fields		100 mT
Limit data		
Operating pressure dynamically		1000 psi
Indicators/operating means		
LED green		Power on
LED yellow		Output status
Standard conformity		
Standards		EN 60947-5-2
Approvals and certificates		
UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Connection type		Connector M12 x 1 , 4-pin
Degree of protection		IP67
Material		Housing: zinc Probe: aluminum
Note		X = 2.062 in (52.4 mm)

Connection



Connection Assignment




Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 904478_eng.pdf

Additional Information

NPT Type Mounting Holes:
1000 and 3000 psi NPT Types:
Mounting hole screw thread shall be 1/4" - 20.
Minimum thread engagement depth is 0.250" (6.35 mm)
Hole spacing is 35 mm center to center.



Mounting Screws:
Standard 1000 and 3000 psi models use two, self-locking 1/4"- 20 socket head cap screws (provided).
Recommended tightening torque: 150 in lb (16.95 N-m).

 **Important:** When using spacers, make certain to maintain the 0.250" (6.35 mm) minimum mounting screw thread engagement.

Accessories

	V1-G-2M-PVC	Female cordset, M12, 4-pin, PVC cable
	SPACER 0.160 TO 0.375 : X.XXX"	Spacer for cylinder switches
	SPACER 0.380 TO 0.875 : X.XXX"	Spacer for cylinder switches
	SPACER 0.880 TO 1.750 : X.XXX"	Spacer for cylinder switches

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 904478_eng.pdf