




**M30 CYLINDRICAL DIRECT DIFFUSE & RETRO-REFLECTIVE
ULTRASONIC SENSOR WITH TEACH-IN BUTTON**

- M30 ultrasonic sensor with standard housing and with large front with high performances and high sensing distances
- Adjustable hysteresis function: models with double digital programmable output specific for level detection
- Models with voltage or current output: programmable slope to optimize resolution
- Adjustable working area (window mode or object mode) by Teach-in button on all models for a quick and easy installation
- Two multifunction LEDs: orange LED for adjustment procedure and output type and green LED for target alignment
- Plastic and AISI 316L stainless steel housing, plug M12 or cable exit 4 pin



Detection properties

Nominal sensing distance	6000mm
Thermal drift of Sr	±5%
Repeat Accuracy	0,1%valore fondoscala
Beam angle	15° ± 2°
Resolution	0,1%valore fondoscala
Sensitivity adjustment	Teach-in button
Hysteresis	1% valore fondoscala

thermal compensation	Si
Minimum sensing distance (blind zone)	350mm
Linearity error	1% valore fondoscala

Application

Function Principle	Diffuse reflection
--------------------	--------------------

Outputs

Output type	IO-Link/PNP + 4...20mA
Output Function	NO/NC + positive/negative slope
Switching frequency	1Hz
Response time	1s

Electrical data

Operating Voltage	10 - 30Vdc
No-Load supply current	25mA
Load current	100mA
Leakage current	≤ 10µA @ 30Vdc
Output voltage drop	2,2V max @ IL=100mA
Max ripple content	5%
LED indicators	Verde: Eco - Giallo: Uscita
Time delay before availability	≤400ms
Short-circuit protection	Si
Reverse Polarity Protection	Si
Impulsive Overvoltage Protection	Si

Mechanical data

Dimensions	ø 38,8mm / L = 99mm
Weight	170g
Housing Material	PBT
Connections	M12 Plug
Tightening torque	1,5Nm
Operating temperature	-20°C...+70°C
Storage temperature	-30°C...+80°C
Transducer Frequency	75KHz
Diameter/Dimension	M30

Test/Approvals

Approvals	CE cULus
EMC compatibility	IEC 60947-5-2
Shocks and vibrations	IEC EN 60947-5-2 / 7.4

Degree of protection	IP67
----------------------	------

Accessories

Supplied Accessories	2 x M30x1,5 dadi, 2 rosette Ø 30
----------------------	----------------------------------

Generical Data

Dimensions	Ø 38,8mm / L = 99mm
------------	---------------------

Operating Temperature	-20°C...+70°C
-----------------------	---------------

Mechanical Protection	IP67
-----------------------	------

Datasensing S.r.l.

Strada S.Caterina, 235

41122 Modena (MO)

Tel. 059 420411

Fax 059 253973

E-mail info@datasensing.com

date of printing

29/04/2022 11:05:20