



AZM 170-02ZRI-B6L-2197 24 VAC/DC

- Long life
- Compact design
- Manual release
- left-hand model
- Double-insulated
- Individual coding
- High holding force
- 90 mm x 84 mm x 30 mm
- 1 Cable entry M 20 x 1.5
- IDC method of termination
- Coding level "High" according to ISO 14119
- Interlock with protection against incorrect locking.
- For very small actuating radii in line with or at 90° to the plane of the actuator

Data

Ordering data

	AZM 170-02ZRI-B6L-2197 24 VAC/DC
	101144353
EAN (European Article Number)	4030661132945
eCl@ss number, Version 9.0	27-27-26-03

Approval - Standards

cULus
CCC
EAC

General data

	AZM 170i
	EN 60947-5-1
	BG-GS-ET-19
general information	Individual coding
Coding level according to ISO 14119	High
Active principle	electromechanical
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the actuator	Stainless steel
Material of the contacts, electrical	Silver
Gross weight	289 g

General data - Features

Power to unlock	Yes
Manual release	Yes
Number of actuating directions	2
Number of safety contacts	2

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Actuating radius, minimum	50 mm
Mechanical life, minimum	1,000,000 Operations
Clamping force in accordance with ISO14119 F_{zh}	1,000 N
Latching force	30 N
positive break travel	11 mm
Positive break force, minimum	17 N
Actuating speed, maximum	2 m/s

Mechanical data - Connection technique

Terminal Connector	IDC method of termination 1 x 0.75 mm ²
Cable section, maximum	1 x 1.0 mm ² , flexible

Mechanical data - Dimensions

Height of sensor	84 mm
Length of sensor	30 mm
Width of sensor	90 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	6 A
Rated control voltage	24 VAC/DC
Required rated short-circuit current to EN 60947-5-1	1,000 A
Electrical power consumption, maximum	10 W
Switching element	Opener (NC)
Note (Switching element)	Change-over contact with double break, type Zb or 2 NC or 3 NC or 4 NC contacts, with galvanically separated contact bridges
Switching principle	Creep circuit element
Switching frequency	1,000 /h

Electrical data - Safety contacts

Voltage, Utilisation category AC15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	2.5 A

Other data

Note (applications)	sliding safety guard removable guard hinged safety guard
---------------------	--

Scope of delivery

Included in delivery	Slot sealing plugs
Delivery scope of Mounting material	Tamperproof screws

Notes

Note (General)	This type termination (IDC) method enables simple connection of flexible conductors without the need for the use of conductor ferrules
	right
	bottom
Note (Manual release)	For manual release using M5 triangular key, available as accessory Additional manual release on side

Ordering code

Product type description:

AZM 170(1)-(2)Z(3)I(4)-(5)-(6)-(7) (8)

(1)

without IDC method of termination

SK Screw connection

(2)

11 1 NO contacts/1 NC contact

02 2 NC contact

(3)

without Latching force 5 N

R Latching force 30 N

I Individual coding

(4)

without Power to unlock

A Power to lock

(5)

without cable gland

ST M12 x 1 connector

(6)

B1 with actuator B1

B5 with actuator B5

B6L with actuator B6L

B6R with actuator B6R

(7)

without Manual release

2197 Manual release from side (Power to unlock)

1637 Gold-plated contacts

(8)

24VAC/DC Us 24 VAC/DC

110VAC Us 110 VAC

230VAC Us 230 VAC

(1)

11/11 1 NO contact, 1 NC contact / 1 NO contact 1, NC contact

11/02 1 NO contact, 1 NC contact / 2 NC contacts

12/00 1 NO contact, 2 NC contacts / -

12/11 1 NO contact, 2 NC contact / 1 NO contact 1, NC contact

12/02 1 NO contact, 2 NC contact / 2 NC contacts

02/01 2 NC contacts / 1 NC contact

02/10 2 NC contacts, - / 1 NO contact

(2)

without Latching force 5 N
R Latching force 30 N

(3)
without Power to unlock
A Power to lock

(4)
B1 with actuator B1
B5 with actuator B5
B6L with actuator B6L
B6R with actuator B6R

(5)
1637 Gold-plated contacts

(6)
2197 Manual release for Power to unlock

Pictures

Photo/Product/Catalogue



ID: kazm1fi3


| 49,6 kB | .png | 74.083 x 93.486 mm - 210 x 265

Pixel - 72 dpi

| 595,8 kB | .jpg | 262.114 x 331.258 mm - 743 x 939

Pixel - 72 dpi

Dimension/Product/Basic



ID: kazm1gi3

| 195,9 kB | .jpg | 352.778 x 400.403 mm - 1000 x

1135 Pixel - 72 dpi


| 106,0 kB | .cdr |

| 6,2 kB | .png | 74.083 x 83.961 mm - 210 x 238 Pixel

- 72 dpi

Diagramm/Product/Travel

ID: kazm1s01




| 1,8 kB | .png | 74.083 x 26.458 mm - 210 x 75 Pixel - 72 dpi

| 19,5 kB | .cdr |

| 49,4 kB | .jpg | 352.778 x 125.236 mm - 1000 x 355 Pixel - 72 dpi

Graphic/Product/Contact


ID: kazm1k11



| 1,8 kB | .png | 74.083 x 23.989 mm - 210 x 68 Pixel - 72 dpi

| 7,1 kB | .jpg | 74.083 x 23.989 mm - 210 x 68 Pixel - 72 dpi

Dimension/Product/Actuator




ID: 1azm1b07

| 109,6 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 Pixel - 72 dpi

| 10,3 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi


Graphic/Product/Radius



ID: kaz17r01

| 19,8 kB | .cdr |


Graphic/Product/Radius



ID: kaz17r02

| 19,8 kB | .cdr |

Illustration/Product/Function




ID: kazm1a70

| 213,5 kB | .jpg | 352.778 x 656.519 mm - 1000 x 1861 Pixel - 72 dpi

| 6,5 kB | .png | 74.083 x 137.583 mm - 210 x 390 Pixel - 72 dpi

Illustration/Product/Function




ID: kazm1a71

| 4,6 kB | .png | 74.083 x 58.914 mm - 210 x 167 Pixel - 72 dpi

| 113,1 kB | .jpg | 352.778 x 280.811 mm - 1000 x 796 Pixel - 72 dpi

Graphic/Product/Mounting



ID: kazm1m06

| 98,4 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 212021-01-30T20:12:21+01:000801Europe/BerlinSat, 30 Jan 2021 20:12:21

+010021pmSaturday.30pm31Europe/BerlinCET1201Europe/BerlinJanuary2021Sat, 30 Jan 2021 20:12:21
+010001pm31