




Indicative image



LIGHT CURTAINS TYPE 4 ACCORDING TO IEC 61496-1 AND IEC 61496-2

- Compact housing (28 x 30 mm) and no dead zone on cap side
- Resolution 14 mm for finger protection, 20, 30, 40 mm for hand protection, 50, 90 mm for presence control and 2, 3, 4 beams for body protection/access control
- Controlled distance up to: 3, 4, 6, 10, 12 m
- Base, Standard versions and Master, Slave version to connect up to 3 sets in cascade configuration
- Selectable Automatic/Manual Restart and EDM integrated functions (Standard models)
- Selectable controlled distance
- IP69K protection models (LS4_K) and models with integrated heating system to reach -25°C operating temperature (LS4_H)
- Standard M12 da 5 and 8 poles connectors



Detection properties

Nominal sensing distance	≤ 20m
Resolution	20mm
controlled height	910mm
number of rays	90
Effective Aperture Angle	±5°

Application

Function Principle	Emitter + Receiver
--------------------	--------------------

Available functions	Automatic Restart
---------------------	-------------------

Safety parameters

Type	4
SIL	3
SILCL	3
PL	e
PFHd	2,24E-08
Dcavg	93,60%
MTTFd	100
CFF	80%

Outputs

Output type	2 x PNP-NO (OSSD safety output)
Response time	13ms

Electrical data

Operating Voltage	19,2 ... 28,8 Vcc
Load current	≤ 400mA
Time delay before availability	2s
Interference to external light	according to IEC 61496-2
Power Consumption - Receiver	2W (no load)
Power Consumption - Emitter	1W
Equivalent Resistive Load	≥ 60 Ω
Capacitive Load	≥ 0,82 μF
Cabel Length (Power Supply/Output)	≤ 100m
Cable Length for Master Slave Interconnections	≤ 50m


Mechanical data

Dimensions	28mm (front) x 30mm
Connections	M12-5 poles (emitter) M12-5 poles (receiver)
Operating temperature	-10°C ÷ +55°C (no condensation)
Storage temperature	-25°C ÷ +70°C (no condensation)
humidity	95% (no condensation)



Test/Approvals

Approvals	CE, cULus, TÜV
EMC compatibility	According to 2014/30/EU Directive
Shocks and vibrations	according to IEC 61496-1
Degree of protection	IP65, IP67

ELECTRICAL DIAGRAMS OF THE CONNECTIONS



CONNECTOR



Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail info@datasensing.com

16/01/2022 08:54:48