





Indicative image



**LIGHT CURTAINS TYPE 4**

- Type 4 according IEC 61496-1 and IEC 61496-2
- Robust housing(50x60 mm) for applications in presence of heavy shocks and vibrations
- 40 mm resolution for hand protection and 2,3,4 beams for body protection/access control
- Operating distance up to 16 m(standard version) and up to 60 m (LONG RANGE version)
- Integrated functions: MANUAL/AUTOMATIC Restart, EDM and operating distance selectable
- Standard M12 5 poles connector on TX unit and M12 8 poles or M23 9 poles on RX unit



**Detection properties**

|                          |         |
|--------------------------|---------|
| Nominal sensing distance | ≤ 6m    |
| Resolution               | 400mm   |
| controlled height        | 800mm   |
| number of rays           | 3       |
| Effective Aperture Angle | ≤ ±2,5° |

**Application**

|                     |                                                                |
|---------------------|----------------------------------------------------------------|
| Function Principle  | Emitter + Receiver                                             |
| Available functions | Manual/Automatic Restart, EDM, System Status, Muting 2 Sensors |

**Safety parameters**

|      |   |
|------|---|
| Type | 4 |
|------|---|

|       |          |
|-------|----------|
| SIL   | 3        |
| SILCL | 3        |
| PL    | e        |
| PFHd  | 4,92E-09 |
| Dcavg | 98,16%   |
| MTTFd | 100      |
| CFF   | 80%      |

### Outputs

|               |                                 |
|---------------|---------------------------------|
| Output type   | 2 x PNP-NO (OSSD safety output) |
| Response time | 10ms                            |

### Electrical data

|                                    |                          |
|------------------------------------|--------------------------|
| Operating Voltage                  | 19,2 ... 28,8 Vcc        |
| Load current                       | 500mA                    |
| Time delay before availability     | 15s                      |
| Interference to external light     | According to IEC 61496-2 |
| Power Consumption - Receiver       | 6W                       |
| Equivalent Resistive Load          | $\geq 48 \Omega$         |
| Capacitive Load                    | $\geq 2 \mu\text{F}$     |
| Cabel Length (Power Supply/Output) | 100m                     |

### Mechanical data

|                       |                               |
|-----------------------|-------------------------------|
| Dimensions            | 50mm (front)x 60mm            |
| Connections           | M23-19 poles (active element) |
| Operating temperature | 0°C...+55°C                   |
| Storage temperature   | -25°C...+70°C                 |
| humidity              | 95% (no condensation)         |

### Test/Approvals

|                       |                                   |
|-----------------------|-----------------------------------|
| Approvals             | CE, cULus, TÜV                    |
| EMC compatibility     | According to 2014/30/EU Directive |
| Shocks and vibrations | According to IEC 61496-1          |
| Degree of protection  | IP65                              |

### Accessories

|                      |                |
|----------------------|----------------|
| Supplied Accessories | ST 202, ST 203 |
|----------------------|----------------|

### Generical Data

|                       |                       |
|-----------------------|-----------------------|
| Dimensions            | 50mm (front)x 60mm    |
| Operating Temperature | 0°C...+55°C           |
| Humidity              | 95% (no condensation) |

## ELECTRICAL DIAGRAMS OF THE CONNECTIONS

---



For the wiring diagram,  
consult the catalogue  
or manual.

---

### **Datasensing S.r.l.**

Strada S. Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail [info@datasensing.com](mailto:info@datasensing.com)

### **date of printing**

29/04/2022 15:50:13