

RS655-Z22-G115



- Metal enclosure
- Protection class IP66, IP67
- Central connection terminal
- wire pull and breakage detection
- Mechanical switching position indication
- two-side operation / wire up to 2 x 100 m

Data

Ordering data

RS655-Z22-G115

153031644

EAN (European Article Number)

4030661532936

Approval - Standards

TÜV
cULus
CCC

General data

IEC 60947-5-1

IEC 60947-5-5

ISO 13850

EN 620

Enclosure material

Grey cast iron, painted

Material of the contacts, electrical

Silver

Material of the cover

Grey cast iron, painted

Length of the wire, maximum

100 m

General data - Features

Indicator lamp

Yes

Number of auxiliary contacts

2

Number of safety contacts

2

Number of signal lamps

1

Safety appraisal

ISO 13849-1

Mission Time

20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)

100,000 Operations

Mechanical data

Actuating element

Roller lever N300

Mechanical life, minimum

100,000 Operations

Actuation direction

Each time 75° right-hand side and left-hand side rotation

Mechanical data - Connection technique

Terminal Connector

Spring pulley connection

Cable entry

2 x M25 x 1.5

Cable section, minimum

0.5 mm², flexible

Cable section, maximum

2.5 mm², flexible

Ambient conditions

Protection class

IP66 to IEC 60529

IP67 to IEC 60529

Ambient temperature, minimum

-25 °C

Ambient temperature, maximum

+60 °C

I

Ambient conditions - Insulation value

Rated impulse withstand voltage

4 kV

3

Electrical data

Thermal test current

6 A

Utilisation category AC-15

230 VAC

Utilisation category AC-15

3 A

Utilisation category DC-13

24 VDC

Utilisation category DC-13

3 A

Switching principle

Snap switch element

Status indication

Colour of the indicator lamp

Red

Note (LED switching conditions display)

Supply voltage UB: 115 VAC

Other data

Note (applications)

Pull-wire emergency stop switches

Ordering code

Product type description:

RS65(1)-Z22-(2)-(3)

(1)

5 Grey cast iron, painted

6 Thermosetting resin

(2)

(3)

without Standard version (without DuplineSafe® input module)

Pictures

Photo/Product/Catalogue



ID: krs65f03


| 25,5 kB | .png | 74.083 x 45.508 mm - 210 x 129

Pixel - 72 dpi

| 285,2 kB | .jpg | 352.778 x 216.958 mm - 1000 x 615

Pixel - 72 dpi

Dimension/Product/Basic



ID: Krs65g01

| 4,4 kB | .png | 74.083 x 53.975 mm - 210 x 153 Pixel
- 72 dpi

| 121,8 kB | .jpg | 352.778 x 256.117 mm - 1000 x 726

Pixel - 72 dpi

Graphic/Product/Mounting



ID: Krs655m05-

| 33,8 kB | .jpg | 352.778 x 35.278 mm - 1000 x 100

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 242021-01-31T07:08:24+01:000701Europe/BerlinSun, 31 Jan 2021 07:08:24

+010024amSunday.31am31Europe/BerlinCET0801Europe/BerlinJanuary2021Sun, 31 Jan 2021 07:08:24

+010001am31