



## SLC 420-E/R0730-30-69-RFB

- Protection class IP69K
- Resolution 14 mm and 30 mm
- Safety type 4 in accordance with IEC 61496-1
- Protection field height from 170 mm ... 1450 mm

### Data

#### Ordering data

SLC 420-E/R0730-30-69-RFB

101206959

eCl@ss number, Version 9.0

27-27-27-04

#### Approval - Standards

TÜV

cULus

EAC

#### General data

|                        |                                     |
|------------------------|-------------------------------------|
| Product name           | SLC 420 IP 69K Safety light curtain |
|                        | IEC/EN 61496-1/-2                   |
| Enclosure material     | Aluminium                           |
| Gross weight           | 4,750 g                             |
| Reaction time, maximum | 10 ms                               |

#### General data - Features

|                                     |     |
|-------------------------------------|-----|
| Restart interlock (manual reset)    | Yes |
| Beam coding available               | Yes |
| Hide function                       | Yes |
| Integral System Diagnostics, status | Yes |
| Integral System Diagnostics         | Yes |
| Number of beams                     | 36  |
| Number of fail-safe digital outputs | 2   |

## Safety appraisal

|                                                 |                          |
|-------------------------------------------------|--------------------------|
|                                                 | ISO 13849-1              |
|                                                 | IEC 61508                |
| Performance level, up to                        | e                        |
| Control category to EN13849                     | 4                        |
| PFH-value                                       | $6.19 \times 10^{-9}$ /h |
| Safety Integrity Level (SIL),<br>applicable for | 3                        |
| Mission Time                                    | 20 Year(s)               |
| Safety type in accordance with IEC<br>61496-1   | 4                        |

## Mechanical data

|                                                     |           |
|-----------------------------------------------------|-----------|
| Detection ability for test bodies at v<br>= 1.6 m/s | 30 mm     |
| Range, protection field, minimum                    | 300 mm    |
| Range, protection field, maximum                    | 10,000 mm |
| Height of the protection field                      | 730 mm    |
| Wave length of the sensor                           | 880 nm    |

## Mechanical data - Connection technique

|                                             |                                       |
|---------------------------------------------|---------------------------------------|
| Terminal Connector                          | Connector                             |
| Length of cable                             | 5 m                                   |
| Terminal connector, Recipient               | Cable with connector plug M12, 8-pole |
| Terminal, Connector, Transmitter            | Cable with connector plug M12, 4-pole |
| Length of the connectable cable,<br>maximum | 100 m                                 |

## Mechanical data - Dimensions

|                    |        |
|--------------------|--------|
| Diameter of sensor | 60 mm  |
| Height of sensor   | 827 mm |

## Ambient conditions

|                                               |                       |
|-----------------------------------------------|-----------------------|
| Protection class                              | IP69K to IEC/EN 60529 |
| Ambient temperature, minimum                  | -10 °C                |
| Ambient temperature, maximum                  | +50 °C                |
| Storage and transport temperature,<br>minimum | -25 °C                |
| Storage and transport temperature,<br>maximum | +70 °C                |

III

## Electrical data

|                                                 |                     |
|-------------------------------------------------|---------------------|
| Voltage type                                    | DC (direct current) |
| Switching voltage OSSD, HIGH signal             | 24 V                |
| Electrical power consumption of the receiver    | 8 W                 |
| Electrical power consumption of the transmitter | 4 W                 |

## Electrical data - Fail-safe digital outputs

|                                             |        |
|---------------------------------------------|--------|
| Output current, (fail-safe output), maximum | 0.5 A  |
| Versions                                    | p-type |

## Scope of delivery

|                      |                            |
|----------------------|----------------------------|
| Included in delivery | Kit with 2 mounting angles |
|----------------------|----------------------------|

## Accessory

SRB-E 301

## Notes

|                |                                                                                                         |
|----------------|---------------------------------------------------------------------------------------------------------|
| Note (General) | $I_{\text{m}}$ In case of failure (interruption of the 0 V supply) the maximum leakage current is 1 mA. |
|----------------|---------------------------------------------------------------------------------------------------------|

## Ordering code

Product type description:

SLC 420-E/R(1)-(2)-69-RFB

(1)

- 0170** Protection field height 170 mm
- 0250** Protection field height 250 mm
- 0330** Protection field height 330 mm
- 0410** Protection field height 410 mm
- 0490** Protection field height 490 mm
- 0570** Protection field height 570 mm
- 0650** Protection field height 650 mm
- 0730** Protection field height 730 mm
- 0810** Protection field height 810 mm
- 0890** Protection field height 890 mm
- 0970** Protection field height 970 mm

- 1050** Protection field height 1050 mm
- 1130** Protection field height 1130 mm
- 1210** Protection field height 1210 mm
- 1290** Protection field height 1290 mm
- 1370** Protection field height 1370 mm
- 1450** Protection field height 1450 mm

(2)

- 14** Resolution 14 mm (Range 0.3 ... ) 7 m
- 30** Resolution 30 mm (Range 0.3 ... ) 10 m

## Pictures


### Photo/Product/Catalogue



ID: kslc2f02

| 549,9 kB | .jpg | 315.736 x 750.006 mm - 895 x 2126  
Pixel - 72 dpi  
| 43,1 kB | .png | 74.083 x 175.683 mm - 210 x 498  
Pixel - 72 dpi

### Dimension/Product/Basic



ID: 1slc2g05

| 2,5 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel  
- 72 dpi  
| 71,6 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695  
Pixel - 72 dpi  
| 91,4 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 442021-01-31T09:06:44+01:000901Europe/BerlinSun, 31 Jan 2021 09:06:44

+010044amSunday.31am31Europe/BerlinCET0601Europe/BerlinJanuary2021Sun, 31 Jan 2021 09:06:44

+010001am31