



### Main

|                               |                                                             |
|-------------------------------|-------------------------------------------------------------|
| Range of product              | Preventa Safety detection                                   |
| Product or component type     | Guard switch                                                |
| Component name                | XCSPR                                                       |
| Material                      | Plastic                                                     |
| Head type                     | Turret head rotary axis                                     |
| Insulation                    | Double insulated                                            |
| Type of operator              | Spindle 30 mm                                               |
| Electrical connection         | Terminal                                                    |
| Contacts type and composition | 1 NC + 1 NC                                                 |
| Contact operation             | Slow-break                                                  |
| Clamping connection capacity  | 1 x 0.5...2 x 1.5 mm <sup>2</sup> with or without cable end |
| Cable entry                   | 1 entry tapped for Pg 11                                    |
| Number of poles               | 2                                                           |

### Complementary

|                                              |                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable outer diameter                         | 7...10 mm                                                                                                                                                                                                                                                                                                                      |
| Positive opening                             | With NC contact                                                                                                                                                                                                                                                                                                                |
| Tripping angle                               | 5 °                                                                                                                                                                                                                                                                                                                            |
| Mechanical durability                        | 1000000 cycles                                                                                                                                                                                                                                                                                                                 |
| Minimum torque for tripping                  | 0.1 N.m                                                                                                                                                                                                                                                                                                                        |
| Positive opening minimum torque              | 0.25 N.m                                                                                                                                                                                                                                                                                                                       |
| Contact code designation                     | A300, AC-15 (Ue = 120 V, Ie = 6 A) conforming to EN/IEC 60947-5-1<br>A300, AC-15 (Ue = 240 V, Ie = 3 A) conforming to EN/IEC 60947-5-1<br>Q300, DC-13 (Ue = 125 V, Ie = 0.55 A) conforming to EN/IEC 60947-5-1<br>Q300, DC-13 (Ue = 250 V, Ie = 0.27 A) conforming to EN/IEC 60947-5-1                                         |
| [Ithe] conventional enclosed thermal current | 10 A                                                                                                                                                                                                                                                                                                                           |
| [Ui] rated insulation voltage                | 300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14<br>500 V (pollution degree 3) conforming to EN/IEC 60947-1                                                                                                                                                                                                   |
| [Uimp] rated impulse withstand voltage       | 6 kV EN/IEC 60947-5-1                                                                                                                                                                                                                                                                                                          |
| Maximum resistance across terminals          | 30 mOhm conforming to EN/IEC 60947-5-4                                                                                                                                                                                                                                                                                         |
| Short-circuit protection                     | 10 A cartridge fuse type gG (gl)                                                                                                                                                                                                                                                                                               |
| Safety level                                 | Can reach category 4 with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach PL = e with the appropriate monitoring system and correctly wired conforming to EN/ISO 13849-1<br>Can reach SIL 3 with the appropriate monitoring system and correctly wired conforming to IEC 61508 |
| Safety reliability data                      | B10d = 5000000 value given for a life time of 20 years limited by mechanical or contact wear                                                                                                                                                                                                                                   |
| Enclosure material                           | Polyamide PA66 fibre glass impregnated                                                                                                                                                                                                                                                                                         |
| Lever material                               | Stainless steel                                                                                                                                                                                                                                                                                                                |
| Width                                        | 30 mm                                                                                                                                                                                                                                                                                                                          |
| Height                                       | 96 mm                                                                                                                                                                                                                                                                                                                          |
| Depth                                        | 60 mm                                                                                                                                                                                                                                                                                                                          |
| Net weight                                   | 0.105 kg                                                                                                                                                                                                                                                                                                                       |

## Environment

|                                       |                                                                                                                          |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Standards                             | EN/IEC 60947-5-4<br>EN/IEC 60204-1<br>CSA C22.2 No 14<br>EN/ISO 12100<br>EN 1088/ISO 14119<br>EN/IEC 60947-5-1<br>UL 508 |
| Product certifications                | CSA<br>UL<br>BG                                                                                                          |
| Protective treatment                  | TC<br>TH                                                                                                                 |
| Ambient air temperature for operation | -25...70 °C                                                                                                              |
| Ambient air temperature for storage   | -40...70 °C                                                                                                              |
| Vibration resistance                  | 50 gn (f= 10...500 Hz) conforming to IEC 60068-2-6                                                                       |
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27                                                                             |
| Electrical shock protection class     | Class II conforming to EN/IEC 61140                                                                                      |
| IP degree of protection               | IP67 conforming to IEC 60529                                                                                             |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Weight             | 137 g   |
| Package 1 Height             | 3.7 cm  |
| Package 1 width              | 11.5 cm |
| Package 1 Length             | 11.5 cm |

## Offer Sustainability

|                            |                                                                                                                                                                                      |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                |
| REACH Regulation           | <a href="#"> REACH Declaration</a>                                                                |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#"> EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                                                                                  |
| RoHS exemption information | <a href="#"> Yes</a>                                                                              |
| Environmental Disclosure   | <a href="#"> Product Environmental Profile</a>                                                    |
| Circularity Profile        | <a href="#"> End of Life Information</a>                                                          |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|