



BN 75-10Z-1391

- Long life
- Float switch
- 1 Reed contacts
- with Pre-wired cable
- Non-contact principle
- 80 mm x 99,5 mm x 55 mm
- Thermoplastic enclosure
- Available with M12 plug-in connector and pre-wired cable

Data

Ordering data

	BN 75-10Z-1391
	101055744
EAN (European Article Number)	4030661009421
eCl@ss number, Version 9.0	27-27-01-05

General data

	BN 75
Active principle	Magnetic drive
Housing construction form	Special construction
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Plastic
Gross weight	122 g

General data - Features

Number of shutters	1
--------------------	---

Mechanical data

Actuating element	Magnet
Mechanical life, minimum	1,000,000,000 Operations
Hysteresis (Switch distance), maximum	3 mm

Mechanical data - Connection technique

Terminal Connector	Pre-wired cable
--------------------	-----------------

Mechanical data - Dimensions

Height of sensor	99.5 mm
Length of sensor	55 mm
Width of sensor	80 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C

Electrical data

Voltage type	AC (alternating current)
Switching voltage, maximum	220 VAC
Switching current, maximum	1 A
Switching capacity, maximum	60 W
Switching capacity, maximum	60 VA
Switching element	Normally open contact (NO)
Bounce duration, minimum	0.3 ms
Bounce duration, maximum	0.6 ms

Electrical data - Digital Output

Versions	Reed contacts
----------	---------------

Notes

Note (General)	Depending on how the floater is assembled, either a NO contact or a NC contact is possible. The indicated switching points are applicable for water
----------------	--

Pictures

Photo/Product/Catalogue




ID: kbn75f01

| 560,2 kB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 Pixel - 72 dpi

| 48,7 kB | .png | 74.083 x 111.125 mm - 210 x 315 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1bn75g01

| 24,8 kB | .cdr |

| 79,9 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693 Pixel - 72 dpi

| 4,0 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel - 72 dpi


Graphic/Product/Contact



ID: 1bn75k01

| 49,9 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693 Pixel - 72 dpi

Diagramm/Product/Curve



ID: kbn32d01

| 110,5 kB | .jpg | 352.425 x 371.828 mm - 999 x 1054 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 192021-01-31T16:27:19+01:000401Europe/BerlinSun, 31 Jan 2021 16:27:19

+010019pmSunday.31pm31Europe/BerlinCET2701Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:27:19

+010001pm31