

AZM300B-ST-1P2P-N



- Series-wiring
- Compact design
- Manual release
- Power to unlock
- Diagnostic output
- Emergency release
- Actuator monitored
- Connector M12, 8-pole
- Thermoplastic enclosure
- 3 different directions of actuation
- 3 LEDs to show operating conditions
- Universal coding with RFID technology
- Suitable for hinged and sliding guards
- Suitable for mounting to profile systems
- RFID-technology for needs-based protection against tampering

Data

Ordering data

	AZM300B-ST-1P2P-N
	103006867
EAN (European Article Number)	4030661451091
eCl@ss number, Version 9.0	27-27-26-03

Approval - Standards

TÜV
cULus
ECOLAB
EAC
FCC
IC

General data

	AZM 300
	ISO 13849-1
	IEC 61508
	IEC 60947-5-3
	ISO 14119
	IEC 62061
general information	Universal coding

Coding level according to ISO 14119	Low
	RFID
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	650 g
Time to readiness, maximum	5,000 ms
Duration of risk, maximum	200 ms

General data - Features

Power to unlock	Yes
Actuator monitored	Yes
Latching	Yes
Emergency release	Yes
Short circuit detection	Yes
Short-circuit recognition	Yes
Series-wiring	Yes
Safety functions	Yes
Integral System Diagnostics, status	Yes
Number of safety contacts	2

Safety appraisal

ISO 13849-1
IEC 62061
IEC 61508

Safety appraisal - Interlocking

Performance level, up to	e
Control category	4
PFH-value	$5.20 \times 10^{-10} /h$
PFD value	4.50×10^{-5}
Safety Integrity Level (SIL), applicable for	3
Mission Time	20 Year(s)

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Note (Mechanical lifetime)	When using as door hinge: ≥ 50.000 operations (Türmassen ≤ 5 kg and actuating speed ≤ 0.5 m/s)
Switch distance	2 mm
Ensured switch distance "ON" S_{ao}	1 mm
Ensured switch distance "OFF" S_{ar}	20 mm

Clamping force in
accordance with ISO14119 F 1,150 N

zh
Clamping force, maximum F 1,500 N

max
Latching force 50 N

Tightening torque of the
fixing screws, minimum 6 Nm

Tightening torque for the
fixing screws, maximum 7 Nm

Mechanical data - Connection technique

Terminal Connector Connector M12, 8-pole, A-coded

Mechanical data - Dimensions

Height of sensor 126 mm

Length of sensor 35 mm

Width of sensor 85 mm

Ambient conditions

Protection class IP66 to IEC 60529
IP67 to IEC 60529
IP69 to IEC 60529

Ambient temperature,
minimum +0 °C

Ambient temperature,
maximum +60 °C

Storage and transport
temperature, minimum -10 °C

Storage and transport
temperature, maximum +90 °C

Resistance to vibrations to
EN 60068-2-6 10 ... 150 Hz, amplitude 0.35 mm

30 g / 11 ms

III

Ambient conditions - Insulation value

Rated impulse withstand
voltage 0.8 kV

III

3

Electrical data

Operating voltage, minimum 20.4 VDC

Operating voltage, maximum 26.4 VDC

No-load current	100 mA
Required rated short-circuit current to EN 60947-5-1	100 A
Reaction time of actuator, maximum	100 ms
Reaction time of input, maximum	0.5 ms
Switching frequency, maximum	0.5 Hz
Note	Cable length and cable section alter the voltage drop depending on the output current

Electrical data - Solenoid control

	-3 V ... 5 V (Low)
	15 V ... 30 V (High)
Current consumption of the magnet control at 24V	10 mA
	C0
	C1
	C2
	C3

Electrical data - Fail-safe digital inputs

	-3 V ... 5 V (Low)
	15 V ... 30 V (High)
Current consumption of the safety inputs at 24V	5 mA
	C1
	C1
	C2
	C3

Electrical data - Fail-safe digital outputs

Rated operating current (safety outputs)	250 mA
Versions	short-circuit proof, p-type
Voltage drop U_d , maximum	4 V
Current leakage	0.5 mA
Voltage, Utilisation category DC12	24 VDC
Current, Utilisation category DC12	0.3 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.3 A

C2
C1
C2

Electrical data - Diagnostic output

Operating current (diagnostic output)	50 mA
Versions	short-circuit proof, p-type
Voltage drop U_d , maximum	4 V
Voltage, Utilisation category DC12	24 VDC
Current, Utilisation category DC12	0.1 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.1 A

Status indication

Note (LED switching conditions display)	Operating condition: LED green Error / functional defect: LED red Supply voltage UB: LED green
--	--

Pin assignment

PIN 1	A1 Supply voltage UB
PIN 2	X1 Safety input 1
PIN 3	A2 GND
PIN 4	Y1 Safety output 1
PIN 5	OUT Diagnostic output
PIN 6	X2 Safety input 2
PIN 7	Y2 Safety output 2
PIN 8	IN Solenoid control

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

AZ/AZM300-B1

Notes

For doors that are flush with the door frame, the optional mounting plate MP-AZ/AZM300-1 can be used.

Note (General)

For glass and Makrolon doors, the optional mounting kit MS-AZ/AZM300-B1-1 can be used.

As long as the actuating unit remains inserted in the solenoid interlock, the unlocked safety guard can be relocked. In this case, the safety outputs are re-enabled, so that the safety guard must not be opened.

Ordering code

Product type description:

AZM300(1)(2)-ST(3)-(4)-(5)

(1)

Z Guard locking monitored

NB, MBN, BN Actuator monitored

(2)

without Standard coding

I1 Individual coding

I2 Individual coding, multiple teaching

(3)

1P2P 1 p-type diagnostic output and 2 p-type safety outputs

SD2P serial diagnostic output and 2 p-type safety outputs

(4)

without Power to unlock

A Power to lock

(5)


without Manual release

T Emergency exit

N Emergency release

Pictures

Photo/Product/Catalogue



Pixel - 72 dpi

Pixel - 72 dpi

ID: 5azm3g04

Pixel - 72 dpi

ID: kazm3g01

1040 Pixel - 72 dpi

ID: kazm3l01

Pixel - 72 dpi

Photo/Product/Detail



ID: kazm3f30

| 719,9 kB | .jpg | 352.778 x 454.731 mm - 1000 x
1289 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 292021-01-30T18:46:29+01:000601Europe/BerlinSat, 30 Jan 2021 18:46:29

+010029pmSaturday.30pm31Europe/BerlinCET4601Europe/BerlinJanuary2021Sat, 30 Jan 2021 18:46:29
+010001pm31