



IFL20-400-10/01

- AC 2-wire
- Design Ø 40 mm
- Double-insulated
- Wiring compartment
- 1 Cable entry PG9 x 1.5
- Thermoplastic enclosure

Data

Ordering data

	IFL 20-400-10/01
	101056640
EAN (European Article Number)	4030661020594
eCl@ss number, Version 9.0	27-27-01-01

Approval - Standards

CCC

General data

	IFL - Ø 40
	IEC/EN 60947-5-2
	DIN VDE 0660-208
Housing construction form	Cylinder smooth
Installation conditions (mechanical)	not flush
Enclosure material	Plastic
Active area	Plastic
Material of the terminal fixing	Plastic
Gross weight	195 g

General data - Features

Integral System Diagnostics, status	Yes
Number of cable wires	2

Mechanical data

Switch distance 20 mm

Mechanical data - Connection technique

Terminal Connector Screw connection
2 x 1.5 mm²

Mechanical data - Dimensions

Diameter of sensor 40 mm
Height of sensor 57 mm
Length of sensor 108 mm
Width of sensor 40 mm

Ambient conditions

IP65
Ambient temperature, minimum -25 °C
Ambient temperature, maximum +70 °C
II

Ambient conditions - Insulation value

Rated impulse withstand voltage 4 kV

Electrical data

Voltage type AC (alternating current)
Rated supply frequency, minimum 45 Hz
Rated supply frequency, maximum 65 Hz
Operating voltage, minimum 15 V
Operating voltage, maximum 250 V
Operating current, minimum 10 mA
Operating current 500 mA
Switching element NO contact or NC contact
Protection circuit integrated inductive interference protection
Switching frequency, approx. 10 Hz

Electrical data - Digital Output

Voltage drop U_d , maximum 4.5 V
Current at Voltage drop U_d 0.2 A
Versions Two-wire
Current leakage 1 mA

Status indication

Note (Integral System Diagnostics, status) yellow LED

Scope of delivery

Note (included in delivery, number and type) Clamp H 40 is included in delivery

Notes

Note (General) Programmable by repositioning the plug-in jumper at the terminal screws

Ordering code

Product type description:

IFL (1)-(2)-(3)(4)(5)

(1)

20 Switching distance 20 mm

(2)

400 Cylinder, smooth, Ø 40 mm, plastic

(3)

01 Opener (NC)

10 Normally open contact (NO)

10/01 NO contact / NC contact with wiring compartment

11 1 NO contact / 1 NC contact antivalent

(4)

without Cable

T Conductor with strain relief

(5)

N n-type

P p-type

Pictures

Photo/Product/Catalogue




ID: kifl2f04

| 587,2 kB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 Pixel - 72 dpi

| 48,9 kB | .png | 74.083 x 111.125 mm - 210 x 315 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1ifl2g04

| 22,3 kB | .cdr |

| 81,0 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691 Pixel - 72 dpi

| 3,6 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel - 72 dpi

Graphic/Product/Contact



ID: ia2ak06

| 45,9 kB | .jpg | 352.778 x 148.167 mm - 1000 x 420 Pixel - 72 dpi

| 30,9 kB | .cdr |

Illustration/Product/Function



ID: sifl2d01

| 50,1 kB | .jpg | 352.778 x 149.578 mm - 1000 x 424 Pixel - 72 dpi

| 1,4 kB | .png | 74.083 x 31.397 mm - 210 x 89 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 132021-01-31T15:12:13+01:000301Europe/BerlinSun, 31 Jan 2021 15:12:13

+010013pmSunday.31pm31Europe/BerlinCET1201Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:12:13

+010001pm31