



SLC 425I-E/R0730-30-RFBC

- 1 ... 8 Cycles
- Protection class IP67
- Integrated muting und override function
- Safety type 4 in accordance with IEC 61496-1

Data

Ordering data

	SLC 425I-E/R0730-30-RFBC
	101207556
eCl@ss number, Version 9.0	27-27-27-04

Approval - Standards

TÜV
cULus
EAC

General data

Product name	SLC 425I Safety light curtain
	IEC/EN 61496-1/-2
Enclosure material	Aluminium
Gross weight	3,480 g
Reaction time, maximum	15 ms

General data - Features

Muting function	Yes
Override	Yes
Clock control possible	Yes
Restart interlock (manual reset)	Yes
Beam coding available	Yes
Hide function	Yes
Integral System Diagnostics, status	Yes
Integral System Diagnostics	Yes

Number of beams	36
Number of fail-safe digital outputs	2

Safety appraisal

	ISO 13849-1 IEC 61508
Performance level, up to	e
Control category to EN13849	4
PFH-value	7.42×10^{-9} /h
Safety Integrity Level (SIL), applicable for	3
Mission Time	20 Year(s)
Safety type in accordance with IEC 61496-1	4

Mechanical data

Detection ability for test bodies at v = 1.6 m/s	30 mm
Range, protection field, minimum	300 mm
Range, protection field, maximum	10,000 mm
Height of the protection field	730 mm
Wave length of the sensor	880 nm

Mechanical data - Connection technique

Terminal Connector	Connector
Terminal connector, Recipient	Connector plug M12, 8-pole
Terminal, Connector, Transmitter	Connector plug M12, 4-pole
Length of the connectable cable, maximum	100 m

Mechanical data - Dimensions

Height of transmitter	815 mm
Height of Receiver	879 mm
Diameter of sensor	49 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-10 °C
Ambient temperature, maximum	+50 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C

Electrical data

Voltage type	DC (direct current)
Switching voltage OSSD, HIGH signal	24 V
Electrical power consumption of the receiver	8 W
Electrical power consumption of the transmitter	4 W

Electrical data - Fail-safe digital outputs

Output current, (fail-safe output), maximum	0.5 A
Versions	p-type

Scope of delivery

Included in delivery	Kit with 2 mounting angles
----------------------	----------------------------

Accessory

SRB-E 301

Notes

Note (General)	I_{m} In case of failure (interruption of the 0 V supply) the maximum leakage current is 1 mA.
----------------	---

Ordering code

Product type description:

SLC 425I-E/R(1)-(2)-RFBC

(1)

- 0170** Protection field height 170 mm
- 0250** Protection field height 250 mm
- 0330** Protection field height 330 mm
- 0410** Protection field height 410 mm
- 0490** Protection field height 490 mm
- 0570** Protection field height 570 mm
- 0650** Protection field height 650 mm
- 0730** Protection field height 730 mm
- 0810** Protection field height 810 mm
- 0890** Protection field height 890 mm
- 0970** Protection field height 970 mm

- 1050** Protection field height 1050 mm
- 1130** Protection field height 1130 mm
- 1210** Protection field height 1210 mm
- 1290** Protection field height 1290 mm
- 1370** Protection field height 1370 mm
- 1450** Protection field height 1450 mm
- 1530** Protection field height 1530 mm (only for resolution 30 mm)
- 1610** Protection field height 1610 mm (only for resolution 30 mm)
- 1690** Protection field height 1690 mm (only for resolution 30 mm)
- 1770** Protection field height 1770 mm (only for resolution 30 mm)

(2)

- 14** Resolution 14 mm
- 30** Resolution 30 mm

Pictures


Photo/Product/Catalogue



ID: kslc4f25

| 61,7 kB | .png | 74.083 x 167.217 mm - 210 x 474
Pixel - 72 dpi
| 851,9 kB | .jpg | 313.619 x 708.378 mm - 889 x 2008
Pixel - 72 dpi

Dimension/Product/Basic



ID: 1slc4g05

| 53,8 kB | .cdr |
| 5,4 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi
| 66,4 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 432021-01-31T09:11:43+01:000901Europe/BerlinSun, 31 Jan 2021 09:11:43

+010043amSunday.31am31Europe/BerlinCET1101Europe/BerlinJanuary2021Sun, 31 Jan 2021 09:11:43

+010001am31