



T2S 422-10Y

- 1 Contact
- Metal enclosure
- Protection class IP65
- With large after-travel
- 2 cable entries M 20 x 1.5
- 106 mm x 71 mm x 63 mm (basic component)
- Actuator head with captive stainless steel ball actuator

Data

Ordering data

T2S 422-10Y

101058518

EAN (European Article Number) 4030661253749

eCl@ss number, Version 9.0 27-27-06-01

Approval - Standards

CCC

EAC

General data

Product name	422 plunger 2S
	EN 60947-5-1
Active principle	mechanical
Slide form	Sphere
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	1,010 g

General data - Features

Number of shutters	1
--------------------	---

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 2,000,000 Operations

Mechanical data

Actuating element	Plunger
Mechanical life, minimum	10,000,000 Operations
Actuating angle	20 °
Contact opening	2 x 6 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 1.5 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	133 mm
Length of sensor	63 mm
Width of sensor	106 mm
Diameter of the Plunger	10 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Electrical data

Thermal test current	16 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	4 A
Switching element	Normally open contact (NO)
Note (Switching element)	with double break
Switching principle	Creep circuit element

Notes

Note (General) Actuation from the side of the plunger should be avoided, since this reduces the mechanical life of the position switch.

Ordering code

Product type description:

T(1) 422-(2)Y-(3)

(1)

S Plunger S

2S Telescopic plunger 2S

R Roller plunger R

K Offset roller lever K

J Offset roller lever J

2C Fork lever 2C

L Roller lever L

D Roller lever D

(2)

01 1 NC contact

10 1 NO contact

(3)

T temperature-resistant and tropical version with ceramic insulation for -40 °C ... +200 °C

1276-2 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: kt422f03

| 453,0 kB | .jpg | 228.6 x 306.211 mm - 648 x 868


Pixel - 72 dpi

| 58,5 kB | .png | 74.083 x 99.131 mm - 210 x 281

Pixel - 72 dpi

Dimension/Product/Basic

ID: 1t422g01



| 3,6 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi

| 29,4 kB | .cdr |

| 82,3 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701
Pixel - 72 dpi

Diagramm/Product/Travel


ID: kt422s09



| 838,0 b | .png | 74.083 x 52.564 mm - 210 x 149
Pixel - 72 dpi

| 21,5 kB | .jpg | 352.778 x 88.194 mm - 1000 x 250
Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t422b02

| 59,9 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701
Pixel - 72 dpi

| 3,1 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi

Illustration/Product/Function



ID: 235sz01

| 14,1 kB | .cdr |

| 1,8 kB | .png | 74.083 x 251.883 mm - 210 x 714
Pixel - 72 dpi

| 95,3 kB | .jpg | 352.778 x 1199.444 mm - 1000 x
3400 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 162021-01-31T15:49:16+01:000301Europe/BerlinSun, 31 Jan 2021 15:49:16

+010016pmSunday.31pm31Europe/BerlinCET4901Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:49:16

+010001pm31