

- **Metal enclosure**
- **66,7 mm x 76 mm x 38 mm**



- **Mounting details to EN 50041**
- **Switching points to EN 50041**
- **3 cable entries lateral M 20 x 1.5**
- **Wide range of alternative actuators**
- **Good resistance to oil and petroleum spirit**
- **Actuator heads can be repositioned by 4 x 90°**
- **Snap action with constant contact pressure up to switching point**
- **Actuation from bottom parallel to the switch, therefore only suitable for small housings.**

Ordering data

101084127

4030661065892

27-27-26-01

cULus

CCC

EAC

Product name

Z 355 offset roller lever 3K

Housing construction form

Norm construction design

Enclosure material

Aluminium

Enclosure coating material

painted

Material of the contacts, electrical

Silver

Gross weight

245 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

	BG-GS-ET-15 ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Angle roller lever
Mechanical life, minimum	30,000,000 Operations
Actuating force, minimum	12 N
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note Bounce duration	Bounce duration in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection 0.75 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	121.5 mm
Length of sensor	38 mm
Width of sensor	66.7 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage 6 kV

Electrical data

Thermal test current 10 A
Required rated short-circuit current to EN 60947-5-1 1,000 A
Utilisation category AC-15 230 VAC
Utilisation category AC-15 4 A
Utilisation category DC-13 24 VDC
Utilisation category DC-13 4 A
Switching element NO contact, NC contact
Switching principle Snap switch element
Switching frequency 5,000 /h
Switchover time, maximum 2 ms

Ordering code

Product type description:

(1)(2) 3(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

1K Offset roller lever 1K

3K Angle roller lever 3K

RMS Brass roller

(3)

3 slim design

5 large design

(4)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

01/01 1 NC contact left / 1 NC contact right

12 1 NO contact/2 NC contacts

03 3 NC contact

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)

G24 with LED

(7)

without Cable entry M20

NPT Cable entry NPT 1/2"

ST M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

ST-2310 M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

(8)

2138 Roller lever 7H for position switches with safety function

(9)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: k355kf02

| 85,5 kB | .png | 74.083 x 122.061 mm - 210 x 346

Pixel - 72 dpi

| 565,7 kB | .jpg | 201.083 x 331.964 mm - 570 x 941

Pixel - 72 dpi

Dimension/Product/Basic

