



TK 016-03Y

- 3 Contacts
- Metal enclosure
- 3 Cable entry M 20 x 1.5
- 67 mm x 105 mm x 43 mm (basic component)
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	TK 016-03Y
	101054893
EAN (European Article Number)	4030661002217
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

cULus
CCC
EAC

General data

Product name	016 offset roller lever K EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Light-alloy diecast, paint finish
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	350 g

General data - Features

Number of openers	3
-------------------	---

Mechanical data

Actuating element	Offset roller lever
Mechanical life, minimum	5,000,000 Operations
Actuating angle, from left of switch axis	45 °
Actuating angle, from right of switch axis	30 °
Actuating force	19 N
Contact opening	2 x 2.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	143 mm
Length of sensor	43 mm
Width of sensor	67 mm
Width of Castor	8.5 mm
Diameter of Castor	20 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Electrical data

Thermal test current	10 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	4 A
Switching element	Opener (NC)
Note (Switching element)	with double break
Switching principle	Creep circuit element

Notes

Note (General) Actuation from the right should be avoided, since this reduces the mechanical life of the position switch.

Ordering code

Product type description:

T(1) 016-(2)Y-(3)

(1)

S Plunger S
2S Telescopic plunger 2S
K Offset roller lever K
2K Tilt lever 2K
3K Angle roller lever 3K
8H Roller lever 8H
7H Roller lever 7H
10H Rod lever 10H
H Roller lever H
4H Spring rod lever on shaft 4H
2H Leaf spring lever 2H
3H Roller lever 3H
9H Rod lever 9H
6H Leaf spring lever 6H

(2)

12 1 NO contact/2 NC contacts
21 2 NO contacts/1 NC contact
03 3 NC contact
30 3 NO contacts

(3)

UE Slow action with overlapping contacts
H Slow action with staggered contacts
C Magnetic blow-out

Pictures


Photo/Product/Catalogue



ID: kts16f03

| 859,6 kB | .jpg | 352.425 x 637.469 mm - 999 x 1807
Pixel - 72 dpi
| 74,7 kB | .png | 74.083 x 133.703 mm - 210 x 379
Pixel - 72 dpi


Dimension/Product/Basic



ID: 1t016g01

| 31,6 kB | .cdr |
| 179,1 kB | .jpg | 352.778 x 305.153 mm - 1000 x 865
Pixel - 72 dpi
| 9,1 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi


Diagramm/Product/Travel



ID: kt016s09

| 18,4 kB | .cdr |
| 1,1 kB | .png | 74.083 x 23.636 mm - 210 x 67 Pixel -
72 dpi
| 22,8 kB | .jpg | 352.778 x 112.889 mm - 1000 x 320
Pixel - 72 dpi


Graphic/Product/Contact



ID: k3o--k02

| 65,3 kB | .jpg | 352.778 x 292.806 mm - 1000 x 830
Pixel - 72 dpi
| 18,7 kB | .cdr |

Dimension/Product/Actuator



ID: 1t15kb01

| 4,2 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi

| 88,2 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703
Pixel - 72 dpi

Illustration/Product/Function



ID: 235rz03

| 131,9 kB | .jpg | 352.778 x 773.642 mm - 1000 x 2193 Pixel - 72 dpi

| 15,5 kB | .cdr |

| 2,7 kB | .png | 74.083 x 162.278 mm - 210 x 460
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 302021-01-31T15:26:30+01:00301Europe/BerlinSun, 31 Jan 2021 15:26:30

```
+010030pmSunday.31pm31Europe/BerlinCET2601Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:26:30
+010001pm31
```