

Safety light grid with integrated control unit




SLPC10-4/31

- Sensing range up to 10 m
- 4-radial design
- Beam spacing 300 mm
- Self-monitoring (type 4 according to IEC/EN 61496-1)
- Red transmission light
- Usable with or without start/restart disable
- Integrated relay monitor
- 7-segment diagnostic display
- Integrated function display
- Pre-fault indication
- OSSD outputs as semiconductor or relay outputs



Dimensions



Technical Data

System components

Emitter	SLP10-4-T
Receiver	SLPC10-4-R/31

General specifications

Effective detection range	0.2 ... 10 m
---------------------------	--------------

Release date: 2020-04-27 Date of issue: 2020-04-27 Filename: 111860_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Light source	LED	
Light type		modulated visible red light
Tests	IEC/EN 61496	
Safety type according to IEC/EN 61496		4
Marking	CE	
Target size		static: 32 mm dynamic: 50 mm (at v = 1.6 m/s of the obstacle)
Beam spacing	300 mm	
Number of beams		4
Operating mode	Start/restart disable, relay monitor,	
Angle of divergence		< 5 °
Functional safety related parameters		
Performance level (PL)		PL e
Category	Cat. 4	
Mission Time (T _M)		20 a
PFH _d	3.54 E-9	
B _{10d}		see instruction manuals
Type	4	
Indicators/operating means		
Diagnostics indicator	7-segment display	
Function indicator		LED red: per receiver channel off: interruption flashes: receiver continuously on: reception with sufficient stability control on the front plate: LED red: OSSD off LED green: OSSD on
Pre-fault indicator	LED red next to receiver flashes	
Control elements		10 DIP switch in receiver terminal compartment
Electrical specifications		
Operating voltage	U _B	24 V DC -15% / +25% , galvanically isolated
No-load supply current	I ₀	max. 250 mA
Protection class		III , IEC 61140
Input		
Activation current		approx. 10 mA
Activation time	0.03 ... 1 s	
Test input		Reset-input for system test
Function input	Relay monitor, start release	
Output		
Pre-fault indication output	1 PNP, +U _B -2 V, max. 300 mA	
Safety output		2 relay outputs, force-guided NO-contact
Signal output	1 PNP each, max. 300 mA for start readiness, OSSD on, OSSD off	
Switching voltage		20 ... 60 V DC, 12 ... 25 V AC _{rms}
Switching current	0.01 ... 2 A	
Switching power		100 VA
Response time	40 ms	
Conformity		
Functional safety	ISO 13849-1	
Product standard		EN 61496-1 ; IEC 61496-2
Approvals and certificates		
CE conformity		CE
Approvals	TÜV SÜD	
Ambient conditions		
Ambient temperature	0 ... 50 °C (32 ... 122 °F)	
Storage temperature		-20 ... 70 °C (-4 ... 158 °F)
Relative humidity	max. 95 %, not condensing	

Release date: 2020-04-27 Date of issue: 2020-04-27 Filename: 111860_eng.pdf


Technical Data

Mechanical specifications

Degree of protection	IP65
Connection	M16 cable gland , terminal compartment with cage-terminals, M12-connector for emitter
Connection options	Further electrical connection options on request: Connector DIN 43 651 Hirschmann, emitter: 6-pin+PE, receiver: 11-pin+PE
Material	
Housing	extruded aluminum profile, RAL 1021 (yellow) coated
Optical face	Plastic pane
Mass	Per 3700 g


Connection

Emitter SLP



- T1 - Emitter channel 1
- T2 - Emitter channel 2
- T3 - Emitter channel 3
- T4 - Emitter channel 4
- 0 V

Receiver SLPC







Receiver SLPC (semi-conductor outputs)		Receiver SLPC/31 (relay output)	
		1 - Functional earth	
		2 - 0 V	
		3 - 24 V	
4 - n.c.		4	
5 - -		5	
6 - +		6	
7 - OSSD 1		7	
8 - OSSD 2		8	
		9 - Input, Relay monitor	
		10 - Input, Start release	
		11 - Input, Reset	
		12 - PNP-Output, Soiled optics	
		13 - n.c.	
		14 - PNP-Output, Startup readiness	
		15 - PNP-Output, Indicator OSSD OFF	
		16 - PNP-Output, Indicator OSSD ON	

Characteristic Curve

Characteristic response curve

SLP10-x / SLPC10-x / SLPCM10-x






Accessories

	PG SLP-4	Protective glass panes for SLP series
---	-----------------	---------------------------------------

Additional information

Socket assignment on the front side of the device



T1 - T4 transmitter control

Socket	Function
1	Transmitter channel 1
2	Transmitter channel 2
3	0 V
4	Transmitter channel 3
5	Transmitter channel 4

System accessories

- Mounting set MS SLP
- Profile alignment aid PA SLP/SLC
- Laser alignment aid BA SLP
- Ground pillar UC SLP/SLC
- Housing for pillar
Enclosure UC SLP/SLC
- Collision protector
Damping UC SLP/SLC
- Redirection mirror for multi-side protection of hazardous areas
SLP-4-M