

BNS 40S-12Z-C



- Long life
- no mechanical wear
- Insensitive to soiling
- 88 mm x 27 mm x 14,5 mm
- Stainless steel enclosure
- Concealed mounting possible
- Suitable for food processing industry
- Insensitive to transverse misalignment
- Cable connection suitable for the food industry
- especially easy to clean through concealed threaded holes at the rear

Data

Ordering data

	BNS 40S-12Z-C
	101215518
EAN (European Article Number)	4030661419282
eCl@ss number, Version 9.0	27-27-24-02

Approval - Standards

TÜV
cULus
ECOLAB
EAC

General data

	BNS 40S
	IEC 60947-5-3
	BG-GS-ET-14
Installation conditions (mechanical)	not flush
Enclosure material	Stainless steel (V4A)
Gross weight	213.2 g

General data - Features

Coding	Yes
--------	-----

Concealed, threaded holes on the back	Yes
Prerequisite evaluation unit	Yes
Number of openers	2
Number of shutters	1
Number of cable wires	6

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d- Value Normally-closed contact/Normally open contact (NC/NO)	25,000,000 Operations
---	-----------------------

Mechanical data

Active area	lateral
Actuating element	Magnet
Ensured switch distance "ON" S_{ao}	8 mm
Ensured switch distance "OFF" S_{ar}	18 mm
Direction of motion	Head-on to the active surface

Mechanical data - Connection technique

Terminal Connector	Cable
Length of cable	1 m
Wire cross-section	0.3 mm ²
Wire cross-section	23 AWG
	LiYY

Mechanical data - Dimensions

Height of sensor	27 mm
Length of sensor	14.5 mm
Width of sensor	88 mm

Ambient conditions

	IP69K
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+80 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm
	30 g / 11 ms

Electrical data

Voltage type	AC (alternating current) DC (direct current)
Switching voltage, maximum	100 VAC
Switching voltage, maximum	100 VDC
Switching current, maximum	0.3 A
Switching capacity, maximum	3 W
Switching frequency, maximum	5 Hz

Electrical data - Digital Output

Versions	Miscellaneous, Reed contacts
----------	------------------------------

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

BPS 40S-2
BPS 40S-1-C
BPS 40S-2-C
SRB-E-301ST
SRB-E-201LC

Notes

Note (General)	Contact symbols shown for the closed condition of the guard device. The contact configuration for versions with or without LED is identical.
----------------	---

Circuit example

Note (Wiring diagram)	Contact S21-S22 must be integrated in the safety circuit.
-----------------------	---

Ordering code

Product type description:

BNS 40S-12Z(1)-(2)


(1)

without without LED switching conditions display

G with LED switching conditions display

without with countersunk mounting holes Ø 4.2 mm
C concealed threaded holes on the back M4

Photo/Product/Catalogue



| 2,9 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi


| 22,5 kB | .cdr |

| 60,5 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695
Pixel - 72 dpi

| 91,7 kB | .jpg | 352.778 x 112.536 mm - 1000 x 319
Pixel - 72 dpi
| 25,4 kB | .cdr |

| 45,4 kB | .cdr |
| 151,1 kB | .jpg | 352.778 x 220.486 mm - 1000 x 625
Pixel - 72 dpi
| 14,0 kB | .png | 74.083 x 46.214 mm - 210 x 131
Pixel - 72 dpi

Diagramm/Product/Curve



ID: kbns4d02

| 14,3 kB | .png | 74.083 x 46.919 mm - 210 x 133

Pixel - 72 dpi

| 46,9 kB | .cdr |

| 147,9 kB | .jpg | 352.778 x 223.661 mm - 1000 x 634

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 242021-01-31T06:33:24+01:000601Europe/BerlinSun, 31 Jan 2021 06:33:24

+010024amSunday.31am31Europe/BerlinCET3301Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:33:24

+010001am31