



TK256-11Z-M20

- Double-insulated
- Thermoplastic enclosure
- 58 mm x 50,5 mm x 31 mm
- 2 cable entries M 20 x 1.5
- Mounting details to EN 50047
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	TK 256-11Z
	101112703
EAN (European Article Number)	4030661073798
eCl@ss number, Version 9.0	27-27-26-01

Approval - Standards

cULus
cCSAus
CCC
EAC

General data

Product name	T 256 offset roller lever K IEC 60947-5-1 ISO 13849-1 BG-GS-ET-15
Housing construction form	Norm construction design
Actuator type to DIN EN 50047	E
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	76 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Offset roller lever
Mechanical life, minimum	20,000,000 Operations
Actuating force, minimum	9 N
Positive break force, minimum	19 N
Actuating speed, minimum	240 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note Bounce duration	Bounce duration in accordance with actuating speed
Note (Switchover time)	Switchover time in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection 0.75 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	82.1 mm
Length of sensor	31 mm
Width of sensor	58 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage 6 kV

Electrical data

Thermal test current 10 A
Required rated short-circuit current to EN 60947-5-1 1,000 A
Utilisation category AC-15 230 VAC
Utilisation category AC-15 4 A
Utilisation category DC-13 24 VDC
Utilisation category DC-13 1 A
Switching element NO contact, NC contact
Switching principle Creep circuit element
Switching frequency 5,000 /h

Ordering code

Product type description:

(1)(2) 2(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

4S Plunger 4S

4R Roller plunger 4R

1R Offset roller lever 1R

K Offset roller lever K

3K Angle roller lever 3K

4K Angle roller lever 4K

K4 Angle roller lever K4

1H Roller lever 1H

7H Roller lever 7H

10H Rod lever 10H

12H Roller lever 12H

14H Roller lever 14H

AF Spring rod lever AF

RMS Brass roller

(3)

3 slim design

5 large design

(4)

02 2 NC contact

11 1 NO contacts/1 NC contact

20 2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)

without Cable entry M20

ID IDC method of termination

NPT Cable entry NPT 1/2"

ST M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

ST-2310 M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

(7)

2574 Enclosure with L-shaped mounting holes (horizontally or vertically adjustable)

(8)

2138 Roller lever 7H for position switches with safety function

(9)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue




ID: k256kf01

| 94,3 kB | .png | 74.083 x 101.6 mm - 210 x 288 Pixel
- 72 dpi

| 420,6 kB | .jpg | 176.036 x 241.653 mm - 499 x 685
Pixel - 72 dpi

Diagramm/Product/Travel

ID: kk235s14




| 1,7 kB | .png | 74.083 x 22.931 mm - 210 x 65 Pixel - 72 dpi

| 46,7 kB | .jpg | 352.778 x 109.714 mm - 1000 x 311 Pixel - 72 dpi

| 25,1 kB | .cdr |


Graphic/Product/Contact



ID: k1o1sk01

| 52,2 kB | .jpg | 352.778 x 143.581 mm - 1000 x 407 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1k236g01

| 3,6 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi

| 67,4 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697 Pixel - 72 dpi

| 60,3 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 072021-01-31T04:16:07+01:000401Europe/BerlinSun, 31 Jan 2021 04:16:07

+010007amSunday.31am31Europe/BerlinCET1601Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:16:07

+010001am31