

TV10H 255-02ZH



- Metal enclosure
- 63 mm x 63,5 mm x 30 mm
- only for positioning tasks
- 3 cable entries M 20 x 1.5
- Mounting details to EN 50047
- Wide range of alternative actuators
- Lever angle adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

TV10H 255-02ZH

101174958

eCl@ss number, Version 9.0

27-27-06-01

General data

Product name	T 255 rod lever 10H
	IEC 60947-5-1
	ISO 13849-1
	BG-GS-ET-15
Housing construction form	Norm construction design
Enclosure material	Zink
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Lever material	Metal film
Material of the rod	Plastic

General data - Features

Number of safety contacts	2
---------------------------	---

Safety appraisal

ISO 13849-1

Mission Time	20 Year(s)
--------------	------------

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Rod lever
Mechanical life, minimum	20,000,000 Operations
Actuating speed, minimum	4,122 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note Bounce duration	Bounce duration in accordance with actuating speed
Note (Switchover time)	Switchover time in accordance with actuating speed
Actuating torque, minimum	0.2 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection 0.75 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Length x Width x Height	Height of sensor: 98.5 mm (without rod)
Length of sensor	43.5 mm
Width of sensor	63 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC

Utilisation category DC-13	1 A
Switching element	Opener (NC)
Switching principle	Slow action with staggered contacts
Switching frequency	5,000 /h

Ordering code

Product type description:

(1)(2) 2(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

4S Plunger 4S

4R Roller plunger 4R

1R Offset roller lever 1R

K Offset roller lever K

3K Angle roller lever 3K

4K Angle roller lever 4K

K4 Angle roller lever K4

1H Roller lever 1H

7H Roller lever 7H

10H Rod lever 10H

12H Roller lever 12H

14H Roller lever 14H

AF Spring rod lever AF

RMS Brass roller

(3)

3 slim design

5 large design

(4)

02 2 NC contact

11 1 NO contacts/1 NC contact

20 2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)	
without	Cable entry M20
ID	IDC method of termination
NPT	Cable entry NPT 1/2"
ST	M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)
ST-2310	M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

(7)

2574 Enclosure with L-shaped mounting holes (horizontally or vertically adjustable)


(8)


2138 Roller lever 7H for position switches with safety function

(9)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue	
	ID: k255hf03
	81,1 kB .png 74.083 x 232.481 mm - 210 x 659 Pixel - 72 dpi
	65,6 kB .png 15.917 x 50.038 mm - 188 x 591 Pixel - 300 dpi
	1,1 MB .jpg 338.667 x 1063.272 mm - 960 x 3014 Pixel - 72 dpi
Diagramm/Product/Travel	
	ID: kh235s10
	1,6 kB .png 74.083 x 23.989 mm - 210 x 68 Pixel - 72 dpi
	16,0 kB .cdr
	46,3 kB .jpg 352.778 x 115.006 mm - 1000 x 326 Pixel - 72 dpi
Graphic/Product/Contact	




ID: k2o--k01

| 48,8 kB | .jpg | 352.778 x 125.236 mm - 1000 x 355

Pixel - 72 dpi

| 1,4 kB | .png | 74.083 x 26.458 mm - 210 x 75 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1h236g03

| 72,1 kB | .cdr |

| 3,9 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

| 83,4 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 452021-01-31T04:05:45+01:00401Europe/BerlinSun, 31 Jan 2021 04:05:45

```
+010045amSunday.31am31Europe/BerlinCET0501Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:05:45
+010001am31
```