



## TV14H 255-02Z

- Metal enclosure
- 63 mm x 63,5 mm x 30 mm
- 3 cable entries M 20 x 1.5
- Mounting details to EN 50047
- Wide range of alternative actuators
- Lever angle adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

## Data

### Ordering data

TV14H 255-02Z

101174975

eCI@ss number, Version 9.0

27-27-26-01

### General data

|                                      |                                                                        |
|--------------------------------------|------------------------------------------------------------------------|
| Product name                         | T 255 roller lever 14 H<br>IEC 60947-5-1<br>ISO 13849-1<br>BG-GS-ET-15 |
| Housing construction form            | Norm construction design                                               |
| Enclosure material                   | Zink                                                                   |
| Enclosure coating material           | painted                                                                |
| Material of the contacts, electrical | Silver                                                                 |
| Lever material                       | Metal film                                                             |
| Roller material                      | Plastic                                                                |

### General data - Features

|                           |     |
|---------------------------|-----|
| Safety functions          | Yes |
| Number of safety contacts | 2   |

### Safety appraisal

ISO 13849-1

|              |            |
|--------------|------------|
| Mission Time | 20 Year(s) |
|--------------|------------|

#### **Safety appraisal - Safety outputs**

|                                   |                       |
|-----------------------------------|-----------------------|
| B10d Normally-closed contact (NC) | 20,000,000 Operations |
|-----------------------------------|-----------------------|

#### **Mechanical data**

|                           |                                                         |
|---------------------------|---------------------------------------------------------|
| Actuating element         | Roller lever                                            |
| Mechanical life, minimum  | 20,000,000 Operations                                   |
| Actuating speed, minimum  | 4,122 mm/min                                            |
| Actuating speed, maximum  | 1 m/s                                                   |
| Note (Actuating speed)    | Actuating speed with actuating angle 30° to switch axis |
| Note Bounce duration      | Bounce duration in accordance with actuating speed      |
| Note (Switchover time)    | Switchover time in accordance with actuating speed      |
| Actuating torque, minimum | 0.2 Nm                                                  |
| Positive break torque     | 0.2 Nm                                                  |

#### **Mechanical data - Connection technique**

|                      |                                                                               |
|----------------------|-------------------------------------------------------------------------------|
| Terminal Connector   | Screw connection<br>0.75 mm²<br>2.5 mm²                                       |
| Note (Cable section) | All indications about the cable section are including the conductor ferrules. |

#### **Mechanical data - Dimensions**

|                  |        |
|------------------|--------|
| Height of sensor | 114 mm |
| Length of sensor | 46 mm  |
| Width of sensor  | 63 mm  |

#### **Ambient conditions**

|                              |        |
|------------------------------|--------|
|                              | IP67   |
| Ambient temperature, minimum | -30 °C |
| Ambient temperature, maximum | +80 °C |

#### **Ambient conditions - Insulation value**

|                                 |      |
|---------------------------------|------|
| Rated impulse withstand voltage | 6 kV |
|---------------------------------|------|

#### **Electrical data**

|                                                      |         |
|------------------------------------------------------|---------|
| Thermal test current                                 | 10 A    |
| Required rated short-circuit current to EN 60947-5-1 | 1,000 A |
| Utilisation category AC-15                           | 230 VAC |
| Utilisation category AC-15                           | 4 A     |

|                            |                       |
|----------------------------|-----------------------|
| Utilisation category DC-13 | 24 VDC                |
| Utilisation category DC-13 | 1 A                   |
| Switching element          | Opener (NC)           |
| Switching principle        | Creep circuit element |
| Switching frequency        | 5,000 /h              |

## Ordering code

Product type description:

(1)(2) 2(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

**Z** Snap action

**T** Slow action (not available for AF/S)

(2)

**S** Plunger S

**R** Roller plunger R

**4S** Plunger 4S

**4R** Roller plunger 4R

**1R** Offset roller lever 1R

**K** Offset roller lever K

**3K** Angle roller lever 3K

**4K** Angle roller lever 4K

**K4** Angle roller lever K4

**1H** Roller lever 1H

**7H** Roller lever 7H

**10H** Rod lever 10H

**12H** Roller lever 12H

**14H** Roller lever 14H

**AF** Spring rod lever AF

**RMS** Brass roller

(3)

**3** slim design

**5** large design

(4)

**02** 2 NC contact

**11** 1 NO contacts/1 NC contact

**20** 2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)

(5)

**H** Slow action with staggered contacts

**UE** Slow action with overlapping contacts

- (6)
- without** Cable entry M20
- ID** IDC method of termination
- NPT** Cable entry NPT 1/2"
- ST** M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)
- ST-2310** M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

- (7)
- 2574** Enclosure with L-shaped mounting holes (horizontally or vertically adjustable)

- (8)
- 2138** Roller lever 7H for position switches with safety function

- (9)
- 1637** Gold-plated contacts

Pictures

Photo/Product/Catalogue




ID: k255hf05

| 73,2 kB | .png | 73.731 x 121.708 mm - 209 x 345  
Pixel - 72 dpi

| 928,9 kB | .jpg | 338.667 x 557.742 mm - 960 x 1581  
Pixel - 72 dpi

Diagramm/Product/Travel




ID: kh235s01

| 26,1 kB | .cdr |

| 73,9 kB | .jpg | 352.778 x 114.653 mm - 1000 x 325  
Pixel - 72 dpi

| 2,4 kB | .png | 74.083 x 23.989 mm - 210 x 68 Pixel -  
72 dpi

Graphic/Product/Contact




ID: k2o--k01

| 48,8 kB | .jpg | 352.778 x 125.236 mm - 1000 x 355

Pixel - 72 dpi

| 1,4 kB | .png | 74.083 x 26.458 mm - 210 x 75 Pixel -  
72 dpi

#### Dimension/Product/Actuator



ID: 1h236g05

| 25,9 kB | .cdr |

| 82,4 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695

Pixel - 72 dpi

| 7,6 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel  
- 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 012021-01-31T04:08:01+01:000401Europe/BerlinSun, 31 Jan 2021 04:08:01

+010001amSunday.31am31Europe/BerlinCET0801Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:08:01

+010001am31