

- Metal enclosure
- 66,7 mm x 76 mm x 38 mm



- **Mounting details to EN 50041**
- **Switching points to EN 50041**
- **3 cable entries lateral M 20 x 1.5**
- **Wide range of alternative actuators**
- **Good resistance to oil and petroleum spirit**
- **Actuator heads can be repositioned by 4 x 90°**
- **Snap action with constant contact pressure up to switching point**

Ordering data

101173410

4030661302515

27-27-26-01

cULus

CCC

EAC

Product name

Z 355 offset roller lever 1K

Housing construction form

Norm construction design

Enclosure material

Aluminium

Enclosure coating material

painted

Material of the contacts, electrical

Silver

Gross weight

240 g

General data - Features

Safety functions	Yes
Number of safety contacts	2

Safety appraisal

	BG-GS-ET-15 ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Offset roller lever
Mechanical life, minimum	30,000,000 Operations
Actuating force, minimum	12 N
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note Bounce duration	Bounce duration in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection 0.75 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	118.5 mm
Length of sensor	38 mm
Width of sensor	66.7 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	Opener (NC)
Switching principle	Snap switch element
Switching frequency	5,000 /h
Switchover time, maximum	2 ms

Ordering code

Product type description:

(1)(2) 3(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

1K Offset roller lever 1K

3K Angle roller lever 3K

RMS Brass roller

(3)

3 slim design

5 large design

(4)

11 1 NO contacts/1 NC contact


02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

01/01 1 NC contact left / 1 NC contact right

12 1 NO contact/2 NC contacts


Diagramm/Product/Travel



ID: kk335s17

| 77,2 kB | .jpg | 352.778 x 190.147 mm - 1000 x 539
Pixel - 72 dpi
| 25,8 kB | .cdr |
| 2,4 kB | .png | 74.083 x 39.864 mm - 210 x 113 Pixel
- 72 dpi


Graphic/Product/Contact



ID: k2o--k01

| 48,8 kB | .jpg | 352.778 x 125.236 mm - 1000 x 355
Pixel - 72 dpi
| 1,4 kB | .png | 74.083 x 26.458 mm - 210 x 75 Pixel -
72 dpi

Dimension/Product/Actuator



ID: 1k336g01

| 71,4 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi
| 7,0 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi
| 57,2 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 272021-01-31T05:05:27+01:000501Europe/BerlinSun, 31 Jan 2021 05:05:27

+010027amSunday.31am31Europe/BerlinCET0501Europe/BerlinJanuary2021Sun, 31 Jan 2021 05:05:27

+010001am31