

ZK 255-02Z



- Metal enclosure
- 63 mm x 63,5 mm x 30 mm
- 3 cable entries M 20 x 1.5
- Mounting details to EN 50047
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°
- Snap action with constant contact pressure up to switching point

Data

Ordering data

	ZK 255-02Z
	101174992
eCl@ss number, Version 9.0	27-27-26-01

General data

Product name	Z 255 offset roller lever K
	IEC 60947-5-1
	ISO 13849-1
	BG-GS-ET-15
Housing construction form	Norm construction design
Actuator type to DIN EN 50047	E
Enclosure material	Zink
Enclosure coating material	painted
Material of the contacts, electrical	Silver

General data - Features

Safety functions	Yes
Number of safety contacts	2

Safety appraisal

ISO 13849-1

Mission Time

20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)

20,000,000 Operations

Mechanical data

Actuating element

Offset roller lever

Mechanical life, minimum

20,000,000 Operations

Actuating force, minimum

9 N

Positive break force, minimum

19 N

Actuating speed, minimum

24 mm/min

Actuating speed, maximum

1 m/s

Note (Actuating speed)

Actuating speed with actuating angle 30° to switch axis

Mechanical data - Connection technique

Terminal Connector

Screw connection

0.75 mm²

2.5 mm²

Note (Cable section)

All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor

95.1 mm

Length of sensor

30 mm

Width of sensor

63 mm

Ambient conditions

IP67

Ambient temperature, minimum

-30 °C

Ambient temperature, maximum

+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage

6 kV

Electrical data

Thermal test current

10 A

Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	Opener (NC)
Switching principle	Snap switch element
Bounce duration, maximum	3 ms
Switching frequency	5,000 /h
Switchover time, minimum	5.5 ms

Pictures

Photo/Product/Catalogue




ID: k255kf01

| 56,9 kB | .png | 73.731 x 100.542 mm - 209 x 285 Pixel - 72 dpi

| 646,3 kB | .jpg | 338.667 x 460.728 mm - 960 x 1306 Pixel - 72 dpi

Diagramm/Product/Travel




ID: kk235s17

| 2,1 kB | .png | 74.083 x 41.275 mm - 210 x 117 Pixel - 72 dpi

| 26,3 kB | .cdr |

| 71,0 kB | .jpg | 352.778 x 196.497 mm - 1000 x 557 Pixel - 72 dpi

Graphic/Product/Contact




ID: k2o--k01

| 48,8 kB | .jpg | 352.778 x 125.236 mm - 1000 x 355 Pixel - 72 dpi

| 1,4 kB | .png | 74.083 x 26.458 mm - 210 x 75 Pixel - 72 dpi

Dimension/Product/Actuator

ID: 1k236g01



| 3,6 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

| 67,4 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi

| 60,3 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 412021-01-31T04:00:41+01:000401Europe/BerlinSun, 31 Jan 2021 04:00:41

+010041amSunday.31am31Europe/BerlinCET0001Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:00:41

+010001am31