



Indicative image

HOLLOW SHAFT ENCODER SERIES FOR INDUSTRIAL APPLICATIONS WITH HIGH MECHANICAL RESISTANCE REQUIREMENTS

- 3 channel encoder (A / B / Z) up to 2500 ppr
- Power supply up to +30 VDC with several electronic outputs available
- Up to 220 kHz output frequency
- Cable or connector output
- Blind hollow shaft diameter up to 15 mm
- Mounting by stator coupling, spring or anti-rotation pin

Detection properties

Resolution	da 100 a 2500 ppr
counting direction	A leads B clockwise (shaft view)

Application

max output frequency	220 kHz
----------------------	---------

Outputs

Output type	push-pull / line driver
-------------	-------------------------

Electrical data

Operating Voltage	5/30 = 4,5 ... 30 V DC (reverse polarity protection)
No-Load supply current	800 mW
max load current	20 mA / channel

Mechanical data

Weight	350 g (12,35 oz)
Housing Material	PA66 glass fiber reinforced
Operating temperature	-20° ... +70°C (-4° ... +158°F)
Storage temperature	-25° ... +70°C (-13° ... +158°F)
max shaft load	200 N

Hole diameter	ø 10 / 15 mm
max rotation speed	3000 rpm
moment of inertia	4 x 10 ⁻⁶ kgm ²
starting torque at 20°C	< 0,02 Nm (IP 54) < 0,06 Nm (IP 66)
Fixing torque for collar clamping	1 Nm max
shaft material	1.4305 / AISI 303 stainless steel
bearings	2 ball bearings
bearings life	109 revolutions

Test/Approvals

EMC compatibility	IEC 61000-6-2 IEC 61000-6-4
Shocks and vibrations	10 G, 10 ... 2000 Hz (IEC 60068-2-6)
Degree of protection	X = IP 54 (IEC 60529) S = IP 66 (IEC 60529)

Generical Data

Operating Temperature	-20° ... +70°C (-4° ... +158°F)
Mechanical Protection	X = IP 54 (IEC 60529) S = IP 66 (IEC 60529)

Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail info@datasensing.com

date of printing

29/04/2022 20:50:08