XZCC20MDM30B

male, 1/2 20UNF, 3-pin, straight connector - cable gland Pg 7



Main	
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Straight male connector 1/2 20 UNF, 3 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal / wire size <0.75 mm² / clamping capacity 36 mm

Complementary

Complementary		
Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
[Ue] rated operational voltage	250 V AC	
[In] rated current	4 A	
Enclosure material	Plastic	
Minimum insulating resistance	1000 GΩ	
Contact resistance	8000 μOhm	
Net weight	0.025 kg	

Environment

2. William City		
IP degree of protection	IP67	
Ambient air temperature for operation	-4085 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	22 g
Package 1 Height	2.2 cm
Package 1 width	3.9 cm
Package 1 Length	9.7 cm
Unit Type of Package 2	S01
Number of Units in Package 2	50
Package 2 Weight	1.355 kg
Package 2 Height	15 cm
Package 2 width	15 cm
Package 2 Length	40 cm

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope


Contractual warranty

Warranty	18 months	
vvariality	10 1110111115	

Product data sheet Dimensions Drawings

XZCC20MDM30B

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Product data sheet Connections and Schema

XZCC20MDM30B

Connections and Schemes

