

# XS7D1A1NAL5DIN

inductive sensor XS7 80x80x26 - PBT -  
Sn40mm - 12..24VDC - cable 5m



## Main

|                                    |                                                         |
|------------------------------------|---------------------------------------------------------|
| Range of product                   | OsiSense XS                                             |
| Series name                        | General purpose                                         |
| Sensor type                        | Inductive proximity sensor                              |
| Device application                 | -                                                       |
| Sensor name                        | XS7                                                     |
| Sensor design                      | Flat form 80 x 80 x 26                                  |
| Size                               | 40 mm                                                   |
| Body type                          | Fixed clippable onto DIN rail                           |
| Detector flush mounting acceptance | Flush mountable                                         |
| Material                           | Plastic                                                 |
| Enclosure material                 | PBT                                                     |
| Type of output signal              | Discrete                                                |
| Wiring technique                   | 3-wire                                                  |
| Discrete output function           | 1 NO                                                    |
| Output circuit type                | DC                                                      |
| Discrete output type               | NPN                                                     |
| Electrical connection              | cable                                                   |
| Cable length                       | 5 m                                                     |
| [Us] rated supply voltage          | 12...24 V DC with reverse polarity protection           |
| Switching capacity in mA           | <= 100 mA DC with overload and short-circuit protection |
| IP degree of protection            | IP68 double insulation conforming to IEC 60529          |

## Complementary

|                          |                              |
|--------------------------|------------------------------|
| Detection face           | Frontal                      |
| Front material           | PBT                          |
| Operating zone           | 0...32 mm                    |
| Differential travel      | 1...15% of Sr                |
| Cable composition        | 3 x 0.34 mm <sup>2</sup>     |
| Wire insulation material | PvR                          |
| Status LED               | Output state: 1 LED (yellow) |
| Supply voltage limits    | 10...36 V DC                 |
| Switching frequency      | <= 100 Hz                    |
| Maximum voltage drop     | <2 V (closed)                |
| Current consumption      | <= 10 mA no-load             |
| Maximum delay first up   | 30 ms                        |
| Maximum delay response   | 5 ms                         |
| Maximum delay recovery   | 35 ms                        |
| Marking                  | CE                           |
| Depth                    | 40 mm                        |
| Height                   | 80 mm                        |
| Width                    | 80 mm                        |

## Environment

|                                       |                                                                         |
|---------------------------------------|-------------------------------------------------------------------------|
| Product certifications                | C-Tick<br>UL<br>CSA                                                     |
| Ambient air temperature for operation | -25...70 °C                                                             |
| Ambient air temperature for storage   | -40...85 °C                                                             |
| Vibration resistance                  | 25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27                            |


## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 0.460 kg |
| Package 1 Height | 1.480 dm |
| Package 1 width  | 0.800 dm |
| Package 1 Length | 0.800 dm |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions



---

## Setting-up

---

### Minimum Mounting Distances (mm)

Side by Side




$e(1) \geq 120$

Face to Face



$e(2) \geq 300$

Facing a Metal Object




$e(3) \geq 120$

---

## Wiring Schemes

---

### NPN



BU : Blue  
BN : Brown  
BK : Black