



## NBGLC33.3/NSK

- **Protection class IP69K**
- **Stainless steel enclosure**
- **for application in food producing machinery**
- **Variable sizes with up to five holes for command devices**
- **No additional mounting accessories such as spacers required thanks to flange seal under the enclosure**

### Data

#### Ordering data

NBGLC33.3/NSK  
 103032719  
 EAN (European Article Number) 4030661531939  
 eCI@ss number, Version 9.0 27-37-12-05

#### General data

|                                            |                 |
|--------------------------------------------|-----------------|
| Enclosure material                         | Stainless steel |
| Colour of the bottom part of the enclosure | Silver          |
| Colour of the sealing                      | Blue            |
| Gross weight                               | 1,265 g         |

#### General data - Features

|                             |   |
|-----------------------------|---|
| Number of cable glands      | 1 |
| Number of command positions | 3 |

#### Mechanical data

|                             |                |
|-----------------------------|----------------|
| Position of the cable gland | mounting holes |
|-----------------------------|----------------|

#### Mechanical data - Connection technique

|                             |         |
|-----------------------------|---------|
| Diameter of the cable gland | 20.3 mm |
|-----------------------------|---------|

## Mechanical data - Dimensions

|       |        |
|-------|--------|
| Width | 100 mm |
| Depth | 195 mm |

## Ambient conditions

|                              |        |
|------------------------------|--------|
|                              | IP67   |
|                              | IP69K  |
| Ambient temperature, minimum | -25 °C |
| Ambient temperature, maximum | +80 °C |

## Pictures

### Photo/Product/Catalogue



ID: knbglf26


| 59,4 kB | .png | 74.083 x 130.881 mm - 210 x 371

Pixel - 72 dpi

| 970,6 kB | .jpg | 352.425 x 623.006 mm - 999 x 1766

Pixel - 72 dpi

### Photo/Product/Catalogue



ID: knbglf53


| 29,4 kB | .png | 74.083 x 71.261 mm - 210 x 202

Pixel - 72 dpi

| 333,0 kB | .jpg | 352.778 x 339.372 mm - 1000 x 962

Pixel - 72 dpi

### Dimension/Product/Basic




ID: knbg3g03

| 86,4 kB | .jpg | 352.778 x 297.039 mm - 1000 x 842

Pixel - 72 dpi

| 2,9 kB | .png | 74.083 x 62.442 mm - 210 x 177 Pixel  
- 72 dpi


## Dimension/Product/Basic



ID: knbg3g09

| 219,4 kB | .jpg | 352.778 x 658.989 mm - 1000 x 1868 Pixel - 72 dpi

## Dimension/Product/Basic



ID: knbg3g10

| 131,4 kB | .jpg | 352.778 x 459.669 mm - 1000 x 1303 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 362021-01-31T14:02:36+01:000201Europe/BerlinSun, 31 Jan 2021 14:02:36

+010036pmSunday.31pm31Europe/BerlinCET0201Europe/BerlinJanuary2021Sun, 31 Jan 2021 14:02:36

+010001pm31