

EX-ZS 355-11Z-3G/D



- Ex certified
- Metal enclosure
- Ex-Zone 2 and 22
- 66,7 mm x 76 mm x 38 mm
- 3 cable entries M 20 x 1.5
- Mounting details to EN 50041
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°
- Including Ex-certified screwed cable gland and screw plug
- Snap action with constant contact pressure up to switching point

Data

Ordering data

	EX-ZS 355-11Z-3G/D
	101193775
EAN (European Article Number)	4030661356914
eCl@ss number, Version 9.0	27-27-26-01

Explosion protection

EN 60079-15
 EN 60079-31
 IEC 60079-0
 22
 2
 3D
 3G
 Ⓜ II 3G Ex nC IIC T5 Gc X
 Ⓜ II 3D Ex tc IIIC T90°C Dc X

Manufacturer declaration	ATEX Zone 2 and 22
--------------------------	--------------------

General data

Product name	EX-Z 355 plunger S IEC 60947-5-1 BG-GS-ET-15
Housing construction form	Norm construction design B
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	283.5 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Plunger
Mechanical life, minimum	30,000,000 Operations
Impact energy, maximum	1 J
Actuating force, minimum	12 N
Actuating speed, maximum	0.5 m/s
Note Bounce duration	Bounce duration in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	7 mm
Cable cross-section of the cable glands, maximum	12 mm
	0.75 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	103.5 mm
Length of sensor	38 mm
Width of sensor	40.5 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Snap switch element
Switching frequency	5,000 /h
Switchover time, maximum	2 ms

Ordering code

Product type description:

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

7H-2138 Roller lever 7H for position switches with safety function

1K Offset roller lever 1K

3K Angle roller lever 3K

11	1 NO contacts/1 NC contact
02	2 NC contact
20	2 NO contacts (not suitable for safety applications)
01/01	1 NC contact left / 1 NC contact right
12	1 NO contact/2 NC contacts
03	3 NC contact

H Slow action with staggered contacts


UE Slow action with overlapping contacts

1297 Enclosure with transverse slotted holes

2138 Roller lever 7H for position switches with safety function

1637 Gold-plated contacts

Photo/Product/Catalogue




| 111,4 kB | .png | 74.083 x 112.183 mm - 210 x 318
Pixel - 72 dpi

| 275,1 kB | .jpg | 127.353 x 192.969 mm - 361 x 547
Pixel - 72 dpi

ID: k-355g01

| 133,4 kB | .jpg | 352.778 x 215.9 mm - 1000 x 612
Pixel - 72 dpi
| 30,4 kB | .cdr |
| 4,4 kB | .png | 74.083 x 45.156 mm - 210 x 128 Pixel
- 72 dpi

Diagramm/Product/Travel




ID: kr335s12

| 67,0 kB | .jpg | 352.778 x 188.031 mm - 1000 x 533
Pixel - 72 dpi
| 2,4 kB | .png | 74.083 x 39.511 mm - 210 x 112 Pixel
- 72 dpi
| 25,9 kB | .cdr |

Dimension/Product/Actuator

ID: 1s336g01



| 2,7 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi
| 48,9 kB | .cdr |
| 52,6 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 382021-01-31T17:45:38+01:000501Europe/BerlinSun, 31 Jan 2021 17:45:38

+010038pmSunday.31pm31Europe/BerlinCET4501Europe/BerlinJanuary2021Sun, 31 Jan 2021 17:45:38

+010001pm31