

### Main

Range of product	OsiSense XU	
Series name	Application	
Electronic sensor type	Photo-electric sensor	
Sensor name	XUY	
Sensor design	Miniature	
Detection system	Thru beam	
Material	Plastic	
Supply circuit type	DC	
Wiring technique	2-wire	
Discrete output function	1 NO or 1 NC programmable	
Electrical connection	1 male connector M8, 4 pins	
Product specific application	Conveyor system and access control series	
Emission	Red LED, pulsed	
[Sn] nominal sensing distance	M polarised reflex     M thru beam     0.08 M diffuse with background suppression     0.25 m diffuse with adjustable sensitivity	

### Complementary

Enclosure material	ABS		
Lens material	PMMA		
Cover material	PUR		
Pulse frequency	6 kHz		
[Us] rated supply voltage	1224 V DC with reverse polarity protection		
Supply voltage limits	1030 V DC		
Switching capacity in mA	100 mA (overload and short-circuit protection)		
Switching frequency	500 Hz		
Maximum voltage drop	<2 V at 100 mA (closed state) <1 V at 10 mA (closed state)		
Current consumption	< 25 mA no-load		
Maximum delay response	1 ms		
Net weight	0.044 kg		

### **Environment**

Product certifications	CE	
1 Todact Certifications		
	CULus	
Ambient air temperature for operation	050 °C	
Ambient air temperature for storage	-2080 °C	
IP degree of protection	IP65 conforming to IEC 60529	
•	IP67 conforming to IEC 60529	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	42.9 g	
Package 1 Height	3.5 cm	
Package 1 width	7 cm	
Package 1 Length	13 cm	

### Offer Sustainability

REACh Regulation	REACh Declaration		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	₫Yes		


### Contractual warranty

Warranty	18 months

# Product data sheet Dimensions Drawings

# XUYECO989

### **Dimensions**



(1) Optical axis

### Product data sheet Connections and Schema

## XUYECO989

### **Connections and Schemes**

### M8



### Transmitter

	BN	10-30 V
	BK	No
	WH	No
	BU	0 V

1/ Brown

BN:

2/ White WH: 3/ Blue

BU: 4/ Black

BK:

Nc: Not connected