

Metal cylindrical shape photoelectric sensors **PR30SL** series


Features

- ◆ Through beam reflection working principle;
- ◆ Excellent anti-interference performance
- ◆ High detection accuracy




Part number

	Emitter	Receiver
NPN/PNP NO/NC	PR30SL-TM100D	PR30SL-TM100DEB
NPN/PNP NO/NC	PR30SL-TM100D 1001	PR30SL-TM100DEB1001
NPN/PNP NO/NC	PR30SL-TM100D1002	PR30SL-TM100DEB 1002

Technical specifications

Detection type	Through beam	Consumption current	≤25mA
Rated distance [Sn]	100m (non-adjustable)	Circuit protection	Short-circuit and reverse polarity
Standard target	> φ15mm opaque object	Response time	< 8.2ms
Light source	Infrared LED (880nm)	Output indicator	Emitter: Green LED Receiver: Yellow LED
Dimensions	M30*99mm	Ambient temperature	-15°C...+55°C
Output	NO/NC (depends on receiver)	Ambient humidity	35-85%RH (non-condensing)
Supply voltage	10...30 VDC	Voltage withstand	1000V/AC 50/60Hz 60s
Min target	Insulation resistance	≥50MΩ(500VDC)
Hysteresis range [%/Sr]	Vibration resistance	10...50Hz (0.5mm)
Repeat accuracy [R]	≤5%	Degree of protection	IP67
Load current	≤200mA (receiver)	Housing material	Nickel-copper alloy
Residual voltage	≤2.5V (receiver)	Connection type	2m PVC cable

Dimensions



Wiring diagram

