



AZM 170Z-ST-FB-ZR-2405

- Long life
- Compact design
- Double-insulated
- High holding force
- 90 mm x 84 mm x 30 mm
- Thermoplastic enclosure
- connector plug M12, 8-pole
- Interlock with protection against incorrect locking.
- Device version for connection to a Safety-Field-Box SFB

Data

Ordering data

	AZM 170Z-ST-FB-ZR-2405
	103038467
EAN (European Article Number)	4030661546537
eCl@ss number, Version 9.0	27-27-26-03

Approval - Standards

EAC

General data

	AZM 170
	EN 60947-5-1
	BG-GS-ET-19
Coding level according to ISO 14119	Low
Active principle	electromechanical
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	329 g

General data - Features

Power to unlock	Yes
Emergency exit	Yes
Number of actuating directions	2
Number of auxiliary contacts	1

Number of safety contacts	2
---------------------------	---

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Clamping force in accordance with ISO14119 F_{zh}	1,000 N
Latching force	5 N
positive break travel	11 mm
Positive break force, minimum	8.5 N
Actuating speed, maximum	2 m/s

Mechanical data - Connection technique

Terminal Connector	Connector plug M12, 8-pole, (A-coding)
--------------------	--

Mechanical data - Dimensions

Height of sensor	92.5 mm
Length of sensor	30 mm
Width of sensor	108 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	6 A
Rated control voltage	24 VDC
Required rated short-circuit current to EN 60947-5-1	1,000 A
Electrical power consumption, maximum	10 W
Switching element	NO contact, NC contact

Note (Switching element)	Change-over contact with double break, type Zb or 2 NC contacts, with galvanically separated contact bridges
Switching principle	Creep circuit element
Switching frequency	1,000 /h

Electrical data - Safety contacts

Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	2 A

Electrical data - Auxiliary contacts

Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	2 A

Other data

Note (applications)	sliding safety guard removable guard hinged safety guard
---------------------	--

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Notes

Note (General)	Individual coding available on request
Note (Emergency exit)	For cases of danger Actuation from within the hazardous area

Ordering code

Product type description:

AZM 170(1)-(2)Z(3)K(4)-(5)-(6)-(7)

(1)

without IDC method of termination

SK Screw connection

(2)

11 1 NO contacts/1 NC contact

02 2 NC contact

(3)

without Latching force 5 N

R Latching force 30 N

I Individual coding

(4)

without Power to unlock

A Power to lock

(5)

without cable gland

ST M12 x 1 connector

ST-2431 Connector M12 x 1, individual solenoid monitoring

(6)

24VAC/DC Us 24 VAC/DC

110VAC Us 110 VAC

230VAC Us 230 VAC

(7)

without Manual release

2197 Manual release from side (Power to unlock)

1637 Gold-plated contacts

(1)

11/11 1 NO contact, 1 NC contact / 1 NO contact 1, NC contact

11/02 1 NO contact, 1 NC contact / 2 NC contacts

12/00 1 NO contact, 2 NC contacts / -

12/11 1 NO contact, 2 NC contact / 1 NO contact 1, NC contact

12/02 1 NO contact, 2 NC contact / 2 NC contacts

02/01 2 NC contacts / 1 NC contact

02/10 2 NC contacts, - / 1 NO contact

(2)

without Latching force 5 N

R Latching force 30 N

(3)

without Power to unlock

A Power to lock

(4)

1637 Gold-plated contacts

(5)

2197 Manual release for Power to unlock

Pictures

Photo/Product/Catalogue



ID: kazm1f84


| 25,8 kB | .png | 74.083 x 53.269 mm - 210 x 151

Pixel - 72 dpi

| 281,6 kB | .jpg | 352.778 x 253.294 mm - 1000 x 718

Pixel - 72 dpi

Dimension/Product/Basic




ID: kazm170fb

| 106,8 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

Graphic/Product/Contact




ID: kazm170fb

| 121,0 kB | .jpg | 352.778 x 273.756 mm - 1000 x 776

Pixel - 72 dpi

Graphic/Product/Contact




ID: kazm170fb-rs

| 125,4 kB | .jpg | 352.778 x 281.517 mm - 1000 x 798

Pixel - 72 dpi

Illustration/Product/Function




ID: kazm1a71

| 4,6 kB | .png | 74.083 x 58.914 mm - 210 x 167 Pixel
- 72 dpi

| 113,1 kB | .jpg | 352.778 x 280.811 mm - 1000 x 796
Pixel - 72 dpi

Graphic/Product/PIN



ID: km23-k8a

| 18,0 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 502021-01-30T19:52:50+01:000701Europe/BerlinSat, 30 Jan 2021 19:52:50

+010050pmSaturday.30pm31Europe/BerlinCET5201Europe/BerlinJanuary2021Sat, 30 Jan 2021 19:52:50
+010001pm31