





Inductive slot sensor GT3,51 50.000/0400

■ 3.5 mm slot width



Dimensions



Technical Data

General specifications

Switching function	Normally open (NO)
Output type	PNP
Slot width	3.5 mm
Depth of immersion (lateral)	4 ... 6 typ. 6 mm
Installation	
Output polarity	DC

Nominal ratings

Operating voltage	U_B	6 ... 30 V
Switching frequency	f	0 ... 2000 Hz
Hysteresis	H	0.15 ... 0.6 mm
Reverse polarity protection		reverse polarity protected
Short-circuit protection		yes
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 100 mA
No-load supply current	I_0	≤ 15 mA

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 416227_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Compliance with standards and directives		
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
CCC approval		CCC approval / marking not required for products rated ≤36 V
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Mechanical specifications		
Housing material		PA 6.6
Degree of protection		IP67
Mass		18 g

Connection



Accessories

	V34-G	Female connector, M9, 4-pin, field attachable
--	-------	---

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 416227_eng.pdf