

BN 325-R-1279



- Long life
- 1 Reed contacts
- Spade connector
- Actuation from front
- Non-contact principle
- 85 mm x 26 mm x 24 mm
- Thermoplastic enclosure
- Cable output left and 2 shielding plates
- Actuating surface and direction of actuation marked by switch symbol

Data

Ordering data

	BN 325-R-1279
	101147091
EAN (European Article Number)	4030661141299
eCl@ss number, Version 9.0	27-27-01-05

General data

	BN 325
Active principle	Magnetic drive
Housing construction form	rectangular
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	98 g

General data - Features

Latching	Yes
Suitable for elevators	Yes
Number of snap-in contacts	1

Mechanical data

Actuating panels	front side
Actuating element	Magnet
Mounting	rear with 2 threaded bolts
Mechanical life, minimum	1,000,000,000 Operations

5 mm ... 55 mm
2 x BP 21S = 20 ... 55 mm
BP 34S = 10 ... 25 mm
BP 10N = 10 mm
BP 10S = 10 mm
2 x BP 10N = 15 mm
2 x BP 10S = 15 mm
BP 15N = 12 mm
BP 15S = 12 mm
2 x BP 15/2N = 17 mm
2 x BP 15/2S = 17mm
BP 34N = 10 ... 25mm
BP 20N = 5 ... 20 mm
BP 20S = 5 ... 20 mm
BP 31N = 5 ... 20 mm
BP 31S = 5 ... 20 mm
BP 11N = 10 mm
BP 11S = 10 mm
2 x BP 11N = 20 mm
2 x BP 11S = 20 mm
BP 12N = 15 mm
BP 12S = 15 mm
2 x BP 12N = 10 ... 25 mm
2 x BP 12S = 10 ... 25 mm
BP 21N = 15 ... 40 mm
BP 21S = 15 ... 40 mm
2 x BP 21N = 20 ... 55 mm

Notice (Switch distance Sn)	Actuating distance up to 55 mm depending on actuating magnet and version. The specified switching distances are applicable for the actuation of individually mounted components without ferromagnetic influence. A change of the distance, either positive or negative, is possible due to ferromagnetic influences. The mutual interference between multiple actuating magnets must be observed.
--------------------------------	---

Repeat accuracy R R 0.3 mm

Actuating speed, maximum	18 m/s
-----------------------------	--------

Mechanical data - Connection technique

Terminal Connector	Cable outlet left and 2 shielding plates
Length of cable	1 m

Mechanical data - Dimensions

Height of sensor	26 mm
Length of sensor	24 mm
Width of sensor	85 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm
	50 g / 11 ms

Electrical data

Switching voltage, maximum	250 VAC
Switching current, maximum	3 A
Switching capacity, maximum	120 VA
Switching element	bistable contact
Bounce duration, minimum	0.3 ms
Bounce duration, maximum	0.6 ms
Switching frequency, maximum	300 Hz

Electrical data - Digital Output

Versions	Reed contacts
----------	---------------

Scope of delivery

Included in delivery Actuators must be ordered separately.

Accessory

BP 10 S
2x BP 10 S
BP 15 S
BP 34 S
BP 20 S
BP 31 S
BP 11 S
2x BP 11 S
BP 12 S
BP 21 S
2x BP 21 S
BP 10 N
2x BP 10 N
BP 15 N
2 x BP 15/2 N
2x BP 15/2 S
BP 34 N
BP 20 N
BP 31 N
BP 11 N
2x BP 11 N
BP 12 N
2x BP 12 N
2x BP 12 S
BP 21 N
2x BP 21 N
BE 20
BE 20 N(S) ST 24VDC
BE 20 N(S) 48VDC
BP 10
2 x BP 15/2
2 x BP 10
BP 15
BP 34

Notes

Note (General) The opening and closing functions depend on the direction of actuation, the actuating magnets and the polarity of the actuating magnets.

Pictures

Photo/Product/Catalogue


ID: kbn32f01



| 15,6 kB | .png | 74.083 x 34.219 mm - 210 x 97 Pixel
- 72 dpi

| 165,3 kB | .jpg | 352.778 x 162.631 mm - 1000 x 461
Pixel - 72 dpi

Dimension/Product/Basic



ID: 1bn32g02

| 78,7 kB | .cdr |
| 7,5 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel - 72 dpi
| 88,8 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693 Pixel - 72 dpi

Diagramm/Product/Travel

ID: ksbn4sx3



| 1,1 kB | .png | 74.083 x 18.697 mm - 210 x 53 Pixel - 72 dpi
| 18,0 kB | .cdr |
| 23,1 kB | .jpg | 352.778 x 88.194 mm - 1000 x 250 Pixel - 72 dpi


Diagramm/Product/Travel

ID: ksbn4sx4



| 18,0 kB | .cdr |
| 1,1 kB | .png | 74.083 x 18.697 mm - 210 x 53 Pixel - 72 dpi
| 22,8 kB | .jpg | 352.778 x 88.194 mm - 1000 x 250 Pixel - 72 dpi


Graphic/Product/Contact



ID: kbn32b02

| 18,8 kB | .cdr |
| 135,1 kB | .jpg | 352.778 x 325.967 mm - 1000 x 924 Pixel - 72 dpi

Diagramm/Product/Curve



ID: kbn32d03

| 116,4 kB | .jpg | 352.425 x 371.828 mm - 999 x 1054
Pixel - 72 dpi

| 3,1 kB | .png | 73.731 x 77.964 mm - 209 x 221 Pixel
- 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 062021-01-31T16:31:06+01:000401Europe/BerlinSun, 31 Jan 2021 16:31:06

+010006pmSunday.31pm31Europe/BerlinCET3101Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:31:06

+010001pm31