

## PS315-T12-J300

- Metal enclosure
- Design to EN 50041
- cable entry 1 x M20 x 1,5
- only for positioning tasks
- Lever angle adjustable in 15° steps
- Simple and quick to adjust the control elements by 45°.
- Quick connection technology as connection terminals rotated by 45°

### Data

#### Ordering data

|                               |                |
|-------------------------------|----------------|
|                               | PS315-T12-J300 |
|                               | 103015128      |
| EAN (European Article Number) | 4030661502991  |

#### Approval - Standards

cULus  
CCC  
EAC

#### General data

|                                      |                           |
|--------------------------------------|---------------------------|
| Product name                         | PS315 with rod lever J300 |
|                                      | IEC 60947-5-1             |
| Housing construction form            | Norm construction design  |
| Enclosure material                   | Metal, zinc die-cast      |
| Enclosure coating material           | painted                   |
| Material of the contacts, electrical | Silver                    |
| Gross weight                         | 384 g                     |

#### General data - Features

|                              |   |
|------------------------------|---|
| Number of auxiliary contacts | 1 |
| Number of safety contacts    | 2 |

## Safety appraisal

ISO 13849-1

Mission Time

20 Year(s)

## Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)

20,000,000 Operations

## Mechanical data

Actuating element

Rod lever J300

Mechanical life, minimum

10,000,000 Operations

Positive break force, minimum

50 N

Actuating speed, minimum

60 mm/min

Actuating speed, maximum

1 m/s

## Mechanical data - Connection technique

Terminal Connector

Screw connection

0.34 mm<sup>2</sup>

1.5 mm<sup>2</sup>

## Mechanical data - Dimensions

Height of sensor

192 mm

Length of sensor

37 mm

Width of sensor

41 mm

## Ambient conditions

IP66

IP67

Ambient temperature, minimum

-30 °C

Ambient temperature, maximum

+80 °C

## Ambient conditions - Insulation value

Rated impulse withstand voltage

4 kV

## Electrical data

Thermal test current

5 A

Required rated short-circuit current to EN 60947-5-1

400 A

Utilisation category AC-15

240 VAC

Utilisation category AC-15

3 A

Utilisation category DC-13

24 VDC

Utilisation category DC-13

3 A

|                     |                             |
|---------------------|-----------------------------|
| Switching element   | 1 NO contact, 2 NC contacts |
| Switching principle | Creep circuit element       |
| Switching frequency | 5,000 /h                    |

## Ordering code

Product type description:

PS(2)-(3)-(4)-(5)-(6)-(7)-(8)-(9)-(10)-(11)-  
(12)

(1)

**without** non-EX version

**EX** Types of protection Ex d and t, to Zone 1/21

**EXI** Types of protection Ex i and t, up to Zone 1/21

(2)

**315** Metal enclosure

**316** Thermoplastic enclosure

(3)

**without** L-hole (standard)

**L** elongated hole

(4)

**Z11** Snap action 1 NO contact / 1 NC contact

**Z02** Snap action 2 NC contacts

**Z12** Snap action 1 NO contact / 2 NC contact

**Z11R** Snap action 1 NO contact / 1 NC contact with latching

**Z01R** Snap action 1 NC contact with latching

**Z02R** Snap action 2 NC contacts with latching

**T11** Slow action 1 NO contact / 1 NC contact

**T02** Slow action 2 NC contacts

**T20** Slow action 2 NO contact

**T12** Slow action 1 NO contact / 2 NC contact

**T21** Slow action 2 NO contact / 1 NC contact

**T03** Slow action 3 NC contacts

**T11UE** Slow action 1 NO contact / 1 NC contact with overlapping contacts

**T02H** Slow action 2 NC contacts with staggered contacts

**T11K** Slow action 1 NO contact + 1 NC contact - short-stroke

**T10** Slow action 1 NO contact

**T02K** Slow action 2 NO contacts short-stroke

**T20H** Slow action 2 NO contacts staggered

(5)

**without** Contacts silver plated (Standard)

- A1** Gold contacts 0,3 µm
- A2** Gold contacts 1,0 µm
- A3** Gold contacts 3,0 µm

(6)

**without** without indication light

**G** integrated status display

(7)

**without** Cable entry M20

**ST** Connector plug M12 - plastic - bottom

**STM** Connector plug M12, metal

(8)

**S200** plunger S200 Ø 6 mm

**S300** Plunger - plastic - tappet width Ø 9 mm

**S310** Plunger - plastic - tappet width Ø 9 mm - with bellows

**R300** Roller plunger - plastic roller - width 4.6 mm

**R302** Roller plunger - brass roller - width 4.6 mm

**R310** Roller plunger - plastic roller - width 4.6 mm

**K360** Angle roller lever with plastic roller Ø 20 mm - left-bent

**K370** Angle roller lever with plastic roller Ø 20 mm - right-bent

**H300** Roller lever - plastic roller Ø 25 mm

**H301** Roller lever - stainless steel roller Ø 25 mm

**H302** Roller lever - brass roller Ø 25 mm

**H310** Roller lever - plastic roller Ø 20 mm

**H311** Roller lever - stainless steel roller Ø 20 mm

**H312** Roller lever - brass roller Ø 20mm

**H326** Roller lever - rubber roller Ø 20mm

**N300** Roller lever - plastic roller Ø 25 mm

**N301** Roller lever - stainless steel roller Ø 20 mm

**N306** Roller lever - rubber roller Ø 50mm

**N360** Roller lever - plastic roller Ø 20 mm - width 9.8 mm - long

**N370** Roller lever - plastic roller Ø 20 mm - width 9.8 mm - very long

**J300** Rod lever - plastic - 200mm -Ø 6mm

**F230** Spring rod - stainless steel - 150.4 mm

**F231** Spring rod - stainless steel - 70.2 mm

**A200** Special actuating bolt - plastic - valve control

(9)

**without** no intent rotation (Standard)

**U1** intent rotation 45°

**U2** intent rotation 90°

**U3** intent rotation 135°

**U4** intent rotation 180°

- U5** intent rotation 225°
- U6** intent rotation 275°
- U7** intent rotation 315°

(10)

**without** no lever rotation (Standard)

- X1** lever rotation 15°
- X2** lever rotation 30°
- X3** lever rotation 45°
- X4** lever rotation 60°
- X5** lever rotation 75°
- X6** lever rotation 90°
- X7** lever rotation 105°
- X8** lever rotation 120°
- X9** lever rotation 135°
- X10** lever rotation 150°
- X11** lever rotation 165°
- X12** lever rotation 180°
- X13** lever rotation 195°
- X14** lever rotation 210°
- X15** lever rotation 225°
- X16** lever rotation 240°
- X17** lever rotation 255°
- X18** lever rotation 270°
- X19** lever rotation 285°
- X20** lever rotation 300°
- X21** lever rotation 315°
- X22** lever rotation 330°
- X23** lever rotation 345°

(11)

**without** Roller outside (Standard)

- I** Roller inside

(12)

**without** -30...+80°C (Standard)

- T** -40...+80°C

(13)

(14)

**without** Zone 2 and 22

**3GD** Zone 2 and 22

**2D** Zone 21

**3D** Zone 22

## Pictures

### Photo/Product/Catalogue



ID: kps3jf01

| 1,0 MB | .jpg | 352.778 x 1172.633 mm - 1000 x 3324 Pixel - 72 dpi

| 65,1 kB | .png | 74.083 x 246.239 mm - 210 x 698 Pixel - 72 dpi

### Photo/Product/Catalogue




ID: kps3jf03

| 40,9 kB | .png | 74.083 x 206.022 mm - 210 x 584 Pixel - 72 dpi

| 606,7 kB | .jpg | 352.778 x 981.781 mm - 1000 x 2783 Pixel - 72 dpi


### Dimension/Product/Basic



ID: kps3xg05

| 123,9 kB | .jpg | 352.778 x 289.278 mm - 1000 x 820 Pixel - 72 dpi


### Diagramm/Product/Travel



ID: kps11s61

| 84,8 kB | .jpg | 352.778 x 173.919 mm - 1000 x 493  
Pixel - 72 dpi  
| 2,3 kB | .png | 74.083 x 36.689 mm - 210 x 104 Pixel  
- 72 dpi


### Graphic/Product/Contact



ID: kps2xk02

| 80,7 kB | .jpg | 352.778 x 148.167 mm - 1000 x 420  
Pixel - 72 dpi

### Dimension/Product/Actuator



ID: kps3xb07

| 148,3 kB | .jpg | 352.778 x 409.928 mm - 1000 x  
1162 Pixel - 72 dpi  
| 4,3 kB | .png | 74.083 x 81.844 mm - 210 x 232 Pixel  
- 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 322021-01-31T02:54:32+01:000201Europe/BerlinSun, 31 Jan 2021 02:54:32

```
+010032amSunday.31am31Europe/BerlinCET5401Europe/BerlinJanuary2021Sun, 31 Jan 2021 02:54:32
+0100001am31
```