



## SLC240COM-ER-1530-30

- Integrated set-up tool
- Process safety with highest availability
- Safety type 2 in accordance with IEC 61496-1
- User-friendly parameter setting, no tools required
- Reliable safety concept in case of interferences (EMC, welding sparks)

### Data

#### Ordering data

|                               |                      |
|-------------------------------|----------------------|
|                               | SLC240COM-ER-1530-30 |
|                               | 103016175            |
| EAN (European Article Number) | 4030661507347        |
| eCl@ss number, Version 9.0    | 27-27-27-04          |

#### Approval - Standards

TÜV  
cULus

#### General data

|                           |                                |
|---------------------------|--------------------------------|
| Product name              | SLC240COM Safety light curtain |
|                           | EN 61496-1                     |
|                           | EN 61496-2                     |
| Master- or Slave-function | Yes                            |
| Enclosure material        | Aluminium                      |
| Gross weight              | 2,440 g                        |
| Reaction time, maximum    | 20 ms                          |

#### General data - Features

|                                     |     |
|-------------------------------------|-----|
| Cascadable                          | Yes |
| Restart interlock (manual reset)    | Yes |
| Hide function                       | Yes |
| Integral System Diagnostics, status | Yes |

|                                     |     |
|-------------------------------------|-----|
| Integral System Diagnostics         | Yes |
| Number of beams                     | 76  |
| Number of fail-safe digital outputs | 2   |

#### Safety appraisal

|                                              |                          |
|----------------------------------------------|--------------------------|
|                                              | ISO 13849-1              |
|                                              | EN 62061                 |
| Performance level, up to                     | c                        |
| Control category to EN13849                  | 2                        |
| PFH-value                                    | $8.05 \times 10^{-9}$ /h |
| Safety Integrity Level (SIL), applicable for | 1                        |
| Mission Time                                 | 20 Year(s)               |
| Safety type in accordance with IEC 61496-1   | 2                        |

#### Mechanical data

|                                                    |           |
|----------------------------------------------------|-----------|
| Detection ability for test bodies at $v = 1.6$ m/s | 30 mm     |
| Range, protection field, minimum                   | 300 mm    |
| Range, protection field, maximum                   | 12,000 mm |
| Height of the protection field                     | 1,530 mm  |
| Wave length of the sensor                          | 880 nm    |

#### Mechanical data - Connection technique

|                                          |                            |
|------------------------------------------|----------------------------|
| Terminal Connector                       | Connector                  |
| Terminal connector, Recipient            | Connector plug M12, 5-pole |
| Terminal, Connector, Transmitter         | Connector plug M12, 4-pole |
| Length of the connectable cable, maximum | 100 m                      |

#### Mechanical data - Dimensions

|                  |          |
|------------------|----------|
| Height of sensor | 1,571 mm |
| Length of sensor | 33 mm    |
| Width of sensor  | 27.8 mm  |

#### Ambient conditions

|                                            |                       |
|--------------------------------------------|-----------------------|
| Protection class                           | IP 67 to IEC/EN 60529 |
| Ambient temperature, minimum               | -10 °C                |
| Ambient temperature, maximum               | +50 °C                |
| Storage and transport temperature, minimum | -25 °C                |
| Storage and transport temperature, maximum | +70 °C                |
|                                            | III                   |

#### Electrical data

|              |                     |
|--------------|---------------------|
| Voltage type | DC (direct current) |
|--------------|---------------------|

|                                                          |      |
|----------------------------------------------------------|------|
| Switching voltage OSSD, HIGH signal                      | 24 V |
| Electrical power consumption of the receiver, maximum    | 10 W |
| Electrical power consumption of the transmitter, maximum | 5 W  |

#### Electrical data - Fail-safe digital outputs

|                                             |        |
|---------------------------------------------|--------|
| Output current, (fail-safe output), maximum | 0.3 A  |
| Versions                                    | p-type |

#### Scope of delivery

|                      |                            |
|----------------------|----------------------------|
| Included in delivery | Kit with 2 mounting angles |
|----------------------|----------------------------|

#### Accessory

SRB-E 301

#### Ordering code

Product type description:

SLC240COM-ER(1)-(2)

(1)

**0330** Protection field height 330 mm

**0410** Protection field height 410 mm

**0490** Protection field height 490 mm

**0570** Protection field height 570 mm

**0650** Protection field height 650 mm

**0730** Protection field height 730 mm

**0810** Protection field height 810 mm

**0890** Protection field height 890 mm

**0970** Protection field height 970 mm

**1050** Protection field height 1050 mm

**1130** Protection field height 1130 mm

**1210** Protection field height 1210 mm

**1290** Protection field height 1290 mm

**1370** Protection field height 1370 mm

**1450** Protection field height 1450 mm

**1530** Protection field height 1530 mm

**1610** Protection field height 1610 mm

**1690** Protection field height 1690 mm

**1770** Protection field height 1770 mm

**1850** Protection field height 1850 mm

**1930** Protection field height 1930 mm

(2)

**14** Resolution 14 mm

**30** Resolution 30 mm

**35** Resolution 35 mm

## Pictures

### Photo/Product/Catalogue




ID: kslc4f67

| 66,6 kB | .png | 74.083 x 254.353 mm - 210 x 721  
Pixel - 72 dpi

| 16,9 kB | .jpg | 79.728 x 273.756 mm - 226 x 776  
Pixel - 72 dpi

| 1.005,9 kB | .jpg | 352.778 x 1212.144 mm - 1000 x  
3436 Pixel - 72 dpi

### Dimension/Product/Basic



ID: 5slc4g23

| 196,0 kB | .jpg | 352.778 x 757.061 mm - 1000 x  
2146 Pixel - 72 dpi

| 5,0 kB | .png | 74.083 x 158.75 mm - 210 x 450 Pixel  
- 72 dpi

### Graphic/Product/Wiring



ID: kslc2l06

| 124,5 kB | .jpg | 352.778 x 475.544 mm - 1000 x  
1348 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 052021-01-31T08:37:05+01:000801Europe/BerlinSun, 31 Jan 2021 08:37:05

+010005amSunday.31am31Europe/BerlinCET3701Europe/BerlinJanuary2021Sun, 31 Jan 2021 08:37:05

+010001am31