



PS116-Z11-STR-K210

- Symmetric enclosure
- Thermoplastic enclosure
- connector plug M12, right
- Protection class IP66, IP67
- Actuator heads can be repositioned by 8 x 45°
- Snap action 1 Normally open contact (NO) / 1 Opener (NC)

Data

Ordering data

	PS116-Z11-STR-K210
	103006602
EAN (European Article Number)	4030661442518
eCl@ss number, Version 9.0	27-27-26-01

Approval - Standards

cULus
CCC
EAC

General data

Product name	PS116 offset roller lever K210
	IEC 60947-5-1
Terminal (mechanical)	right
Housing construction form	Norm construction design
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, zinc die-cast, chromated
Material of the contacts, electrical	Silver
Gross weight	70 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1

Number of safety contacts	1
---------------------------	---

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Offset roller lever K210
Mechanical life, minimum	10,000,000 Operations
Actuating force, minimum	11 N
Positive break force, minimum	40 N
Actuating speed, minimum	27 mm/min
Actuating speed, maximum	1 m/s

Mechanical data - Connection technique

Terminal Connector	Connector M12, 4-pole
--------------------	-----------------------

Mechanical data - Dimensions

Height of sensor	79 mm
Length of sensor	16.6 mm
Width of sensor	31 mm
Diameter of Castor	14 mm

Ambient conditions

	IP66
	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	2.5 kV
---------------------------------	--------

Electrical data

Thermal test current	2.5 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	240 VAC
Utilisation category AC-15	1.5 A

Utilisation category DC-13	24 VDC
Utilisation category DC-13	1.5 A
Switching element	NO contact, NC contact
Switching principle	Snap switch element
Bounce duration, maximum	3 ms
Switching frequency	5,000 /h
Switchover time, maximum	5.5 ms

Ordering code

Product type description:

PS116-(1)-(2)-(3)-(4)

(1)

- Z11** Snap action 1 NO contact / 1 NC contact
- Z02** Snap action 2 NC contacts
- Z12** Snap action 1 NO contact / 2 NC contact
- Z11R** Snap action 1 NO contact / 1 NC contact with latching
- Z02R** Snap action 2 NC contacts with latching
- Z12R** Snap action 1 NO contact / 2 NC contact with latching
- T11** Slow action 1 NO contact / 1 NC contact
- T02** Slow action 2 NC contacts
- T20** Slow action 2 NO contact
- T12** Slow action 1 NO contact / 2 NC contact
- T21** Slow action 2 NO contact / 1 NC contact
- T03** Slow action 3 NC contacts
- T11UE** Slow action 1 NO contact / 1 NC contact with overlapping contacts
- T02H** Slow action 2 NC contacts with staggered contacts

(2)

- L200** Connecting cable bottom, cable length 2 m
- LR200** Connecting cable right, cable length 2 m
- ST** Connector plug M12 - plastic - bottom
- STR** Connector plug M12, right

(3)

- S200** plunger S200 Ø 6 mm
- R200** Roller plunger R200
- K200** Offset roller lever - plastic roller- width 5.3 mm - Ø 12 mm
- K210** Offset roller lever - plastic roller- width 5mm - Ø 14mm
- K230** Angle roller lever - plastic roller Ø 14 mm
- K240** Angle roller lever with plastic roller Ø 22 mm - right-bent
- K250** Angle roller lever with plastic roller Ø 22 mm - left-bent

- H200** Roller lever - plastic roller Ø 16 m - lever length 24 mm
- N200** Roller lever 2 mm Toothing (24...26mm) - Plastic roller Ø 20 mm - Width 9.8 mm
- J200** Rod lever - plastic - 200mm -Ø 6mm

- (4)
- 0** Material Castor/Lever: Plastic
 - 1** Material Castor/Lever: Stainless steel
 - 2** Material Castor/Lever: Brass
 - 3** Material Castor/Lever: Aluminium
 - 4** Material Castor/Lever: Steel

Pictures

Photo/Product/Catalogue




ID: kps1kf10

| 583,4 kB | .jpg | 352.778 x 460.022 mm - 1000 x 1304 Pixel - 72 dpi

| 38,9 kB | .png | 73.731 x 96.308 mm - 209 x 273 Pixel - 72 dpi

Dimension/Product/Basic




ID: kps11g01

| 132,8 kB | .jpg | 352.778 x 279.047 mm - 1000 x 791 Pixel - 72 dpi

| 4,8 kB | .png | 74.083 x 58.561 mm - 210 x 166 Pixel - 72 dpi

Diagramm/Product/Travel



ID: kps11s19

| 74,5 kB | .jpg | 352.778 x 198.261 mm - 1000 x 562 Pixel - 72 dpi

| 2,3 kB | .png | 74.083 x 41.628 mm - 210 x 118 Pixel - 72 dpi

Graphic/Product/Contact

ID: kps16k02


(3) BN 13 — 14 PK (4)
(1) YE 21 — 22 WH (2)

| 1,3 MB | .cdr |

| 56,4 kB | .jpg | 352.778 x 64.206 mm - 1000 x 182

Pixel - 72 dpi

Dimension/Product/Actuator



ID: kps11b05

| 3,8 kB | .png | 74.083 x 59.267 mm - 210 x 168 Pixel
- 72 dpi

| 171,7 kB | .jpg | 352.778 x 281.869 mm - 1000 x 799
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 172021-01-31T02:11:17+01:000201Europe/BerlinSun, 31 Jan 2021 02:11:17

+010017amSunday.31am31Europe/BerlinCET1101Europe/BerlinJanuary2021Sun, 31 Jan 2021 02:11:17

+010001am31