


**NWT21.1**

## Data

### Ordering data

|                               |               |
|-------------------------------|---------------|
|                               | NWT21.1       |
|                               | 101164761     |
| EAN (European Article Number) | 4250116200191 |
| eCl@ss number, Version 9.0    | 27-37-12-13   |

### Approval - Standards

cULus  
 CCC  
 IPA

### General data

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| Product name               | NWT - Selector switch<br>EN 60947-5-1<br>IEC/EN 60947-1 |
| Versions                   | Toggle                                                  |
| Toggle                     | long                                                    |
| Sealing type               | Membrane<br>Lip gaskets                                 |
| Material of the operators  | ABS                                                     |
| Material of the front ring | ABS, chrome-plated                                      |
| Colour of the front ring   | Silver                                                  |
| Colour of the handle       | Grey                                                    |
| Gross weight               | 35 g                                                    |

### General data - Features

|                  |     |
|------------------|-----|
| Probing possible | Yes |
|------------------|-----|

|                            |     |
|----------------------------|-----|
| Fully insulated            | Yes |
| Number of plunger          | 1   |
| Number of switch positions | 2   |

#### Mechanical data

|                                |                     |
|--------------------------------|---------------------|
| Unlocking                      | without             |
| Touch position                 | right               |
| Mounting                       | Mounting flange EFM |
| Switching angle, right         | 55 °                |
| Tightening torque of the screw | 0.6 Nm              |

#### Mechanical data - Dimensions

|                                          |               |
|------------------------------------------|---------------|
| Height                                   | 26 mm         |
| diameters for the actuating heads        | 44.5 mm       |
| Length of the handle                     | 46 mm         |
| Diameter hole                            | 22.3 mm       |
| Diameter hole, with tolerance indication | 22.3 + 0.4 mm |
| Thickness, of the front panel, minimum   | 1.5 mm        |
| Thickness of the front panel, maximum    | 6 mm          |
| Spacing                                  | 50 x 60 mm    |

#### Ambient conditions

|                              |        |
|------------------------------|--------|
|                              | IP67   |
|                              | IP69K  |
| Ambient temperature, minimum | +0 °C  |
| Ambient temperature, maximum | +80 °C |

#### Ordering code

Product type description:

-

|                        |                                                                                                        |
|------------------------|--------------------------------------------------------------------------------------------------------|
| <b>(1)DT(8)(2)</b>     | Pushbutton                                                                                             |
| <b>(1)DM(2)</b>        | Pushbutton with diaphragm for dust protection                                                          |
| <b>(1)DL(8)(2)</b>     | Illuminated pushbutton                                                                                 |
| <b>(1)DLM(2)</b>       | Illuminated pushbutton with diaphragm for dust protection                                              |
| <b>(1)ML(2)</b>        | Indicator light with flat collar                                                                       |
| <b>(1)MLH(2)</b>       | Indicator light with high collar                                                                       |
| <b>(1)DP(3)(8)(2)</b>  | Mushroom head impact button without latching                                                           |
| <b>(1)DTP(3)(8)(2)</b> | Mushroom head impact button without latching (only N-programm)                                         |
| <b>(1)DLP(3)(8)(2)</b> | Mushroom head impact button illuminated, without latching (only N programme)                           |
| <b>(1)DRR(3)(8)(2)</b> | Mushroom head impact button with latching, unlock by turning and pulling (pulling only in N programme) |

|                        |                                                                         |
|------------------------|-------------------------------------------------------------------------|
| <b>(1)DRZ(3)(8)(2)</b> | Mushroom head impact button with latching, unlock by pulling            |
| <b>(1)WS21(4)(5)</b>   | Selector switch with 2 positions:                                       |
| <b>(1)WT21(4)(5)</b>   | Selector switch with 1 momentary position                               |
| <b>(1)WS32(4)(5)</b>   | Selector switch with 3 maintained positions                             |
| <b>(1)WT32(4)(5)</b>   | Wahlschalter mit 2 Taststellungen                                       |
| <b>(1)WST32(4)(5)</b>  | Selector switch: switching, latching                                    |
| <b>(1)WTS32(4)(5)</b>  | Selector switch: latching, switching                                    |
| <b>(1)SS21S(4)(5)</b>  | Key-operated selector switch with 2 maintained positions                |
| <b>(1)ST21S(4)(5)</b>  | Key-operated selector switch with 1 momentary position                  |
| <b>(1)SS32S(4)(5)</b>  | Key-operated selector switch with 3 maintained positions                |
| <b>(1)ST32S(4)(5)</b>  | Key-operated selector switch with 2 momentary positions, left and right |
| <b>(1)SST32S(4)(5)</b> | Key-operated selector switch: switching, latching                       |
| <b>(1)STS32S(4)(5)</b> | Key-operated selector switch: latching, switching                       |
| <b>NB, MBN, BN</b>     | <b>Blanking plug</b>                                                    |

(1)

**- Command and signalling devices:**

**E** "E" program

**N** "N" program

**R** "R" program

(2)

**- Colour of button surface:**

**SW** Black

**GB** Grey

(3)

**- Head diameter of mushroom head impact button 30 mm:**

**30** 30 mm

**35** 35 mm

**40** 40 mm

**42** 42 mm

**45** 45 mm

**50** 50 mm

**55** 55 mm

**70** 70 mm

(4)

**- Toggle length in mm:**

**without** Short toggle

**.1** Long toggle

(5)

**- Colour of toggle:**

**without** Grey

(6)

- **Key-withdrawal position (3 positions):**

**1** Position left

**2** Position middle

**3** Position right

(7)

- **Key-withdrawal position (2 positions):**

**1** Position left

**2** Position right

(8)

- **Colour of diaphragm (only N programme):**

**without** Black

**Pictures**

**Photo/Product/Catalogue**



ID: krw--f03

| 406,1 kB | .jpg | 352.778 x 325.967 mm - 1000 x 924

Pixel - 72 dpi

| 33,8 kB | .png | 74.083 x 68.439 mm - 210 x 194

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 122021-01-31T13:25:12+01:000101Europe/BerlinSun, 31 Jan 2021 13:25:12

+010012pmSunday.31pm31Europe/BerlinCET2501Europe/BerlinJanuary2021Sun, 31 Jan 2021 13:25:12

+010001pm31