



IFL15-300-01T

- AC 2-wire
- Design M30
- Double-insulated
- Thermoplastic enclosure

Data

Ordering data

	IFL 15-300-01T
	101060611
EAN (European Article Number)	4030661047935
eCl@ss number, Version 9.0	27-27-01-01

Approval - Standards

CCC

General data

	IFL - M30
	IEC/EN 60947-5-2
	DIN VDE 0660-208
Housing construction form	Cylinder, thread
Installation conditions (mechanical)	not flush
Enclosure material	Plastic
Active area	Plastic
Material of the nuts	Plastic
Material of the washer	Perbunan [®]
Gross weight	125 g

General data - Features

Integral System Diagnostics, status	Yes
Cable sleeve	Yes
Number of cable wires	2

Mechanical data

Switch distance	15 mm
Tightening torque of nuts, maximum	4 Nm

Mechanical data - Connection technique

Terminal Connector	Cable H03VV-F
Length of cable	2 m
Wire cross-section	0.5 mm ² PVC

Mechanical data - Dimensions

	M30
width across flats	36 BK
Length of sensor	98 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
	II

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Voltage type	AC (alternating current)
Rated supply frequency, minimum	45 Hz
Rated supply frequency, maximum	65 Hz
Operating voltage, minimum	15 V
Operating voltage, maximum	250 V
Operating current, minimum	10 mA
Operating current	500 mA
Switching element	Opener (NC)
Protection circuit integrated	inductive interference protection
Switching frequency, approx.	10 Hz

Electrical data - Digital Output

Voltage drop U_d , maximum	4.5 V
Current at Voltage drop U_d	0.2 A
Versions	Two-wire

Status indication

Note (Integral System Diagnostics, status) yellow LED

Note (General) Instead of nuts, a mounting clamp can be provided.

Ordering code

Product type description:

IFL (1)-(2)(3)-(4)(5)(6)(7)-(8)

10 Switching distance 10 mm

15 Switching distance 15 mm

30 Cylinder, thread M30, metal

300 Cylinder, thread M30, plastic

without Standard body

M Miniature body

L Long design

01 Opener (NC)

10 Normally open contact (NO)

10/01 NO contact / NC contact with wiring compartment

11 1 NO contact / 1 NC contact antiviral

without Cable

ST Male connector

T Conductor with strain relief

D DC 2-wire

without Standard connector version

2 Alternative conector version

N n-type

P p-type

(8)

1310 Can be used up to +110 C (for alternating current (AC) only)

2130 Can be used up to +130 C, without LED switching conditions display

1766 Can be used up to +110 C (for p-type or n-type only)

Pictures

Photo/Product/Catalogue




ID: kifl1f11

| 38,1 kB | .png | 74.083 x 111.125 mm - 210 x 315
Pixel - 72 dpi

| 478,1 kB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1ifl1g16

| 25,5 kB | .cdr |

| 3,9 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 90,2 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

Graphic/Product/Contact



ID: ia2lk02

| 39,0 kB | .jpg | 352.778 x 148.167 mm - 1000 x 420
Pixel - 72 dpi

| 29,6 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 162021-01-31T15:08:16+01:000301Europe/BerlinSun, 31 Jan 2021 15:08:16

+010016pmSunday.31pm31Europe/BerlinCET0801Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:08:16

+010001pm31