


AZM 415-33ZPDKA 24 VAC/DC



- Long life
- Robust design
- Metal enclosure
- for double doors
- Cut clamp termination
- Spring-loaded actuators
- 141 mm x 125 mm x 46,5 mm
- 2 cable entries M 20 x 1.5
- 3 switches in one enclosure
- Interlock with protection against incorrect locking.
- Ball latch for each door, individually adjustable up to 400 N

Data

Ordering data

	AZM 415-33ZPDKA 24 VAC/DC
	101172090
EAN (European Article Number)	4030661299990
eCl@ss number, Version 9.0	27-27-26-03

Approval - Standards

EAC

General data

	AZM 415
	EN 60947-5-1
	BG-GS-ET-19
Active principle	electromechanical
Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	1,230 g

General data - Features

Power to lock	Yes
Number of actuating directions	1

Number of auxiliary contacts	3
Number of safety contacts	3
Number of guard doors	2

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Clamping force in accordance with ISO14119 F_{zh}	2,500 N
Note (Clamping force)	each guard
Latching force, minimum	150 N
Latching force, maximum	400 N
positive break travel	4.5 mm
Positive break force, minimum	15 N
Actuating speed, maximum	0.2 m/s

Mechanical data - Connection technique

Terminal Connector	Screw connection 2 x 0.75 mm ² 2 x 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	125 mm
Length of sensor	46.5 mm
Width of sensor	141 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+50 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	6 A
Rated control voltage	24 VAC/DC
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Electrical power consumption, maximum	10 W
Switching element	NO contact, NC contact
Switching principle	Creep circuit element

Other data

Note (applications)	sliding safety guard hinged safety guard
---------------------	---

Ordering code

Product type description:

AZM 415-(1)(2)PK(3)-(4) (5)(6)-(7)

(1)

11/11 2 NC contacts/2 NO contacts

11/02 3 NC contacts / 1 NO contacts

11/20 1 NC contacts / 3 NO contacts

02/11 3 NC contacts / 1 NO contacts

02/20 2 NC contacts / 2 NO contacts

02/02 4 NC contact

(2)

X Protection class IP54

Z Protection class IP67

(3)

without Power to unlock

A Power to lock

(4)

STR Connector M23 right

ST Connector M23 bottom

(5)

without Without manual release

E	Manual release using triangular key
F	with triangular key (secured with locking screw)
FE	using triangular key
RS	Manual release using key
T	Emergency exit using latched pushbutton (power to unlock only)
TE	Emergency exit using latched pushbutton and manual release, mounting outside (power to unlock only)
TEI	Emergency exit using latched pushbutton and manual release, mounting inside (power to unlock only)
NS	Emergency release using lock button

(6)

24VAC/DC Us: 24 VAC/DC

110VAC Us: 110 VAC

230VAC Us: 230 VAC

(7)

1637 Gold-plated contacts

(1)

A Power to lock

(2)

ST Connector M23 right

without Power to unlock

STR Connector M23 bottom

(3)

without Without manual release

E Manual release using triangular key (only for power to unlock principle)

(4)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: kazm4f23


| 29,0 kB | .png | 74.083 x 50.094 mm - 210 x 142

Pixel - 72 dpi

| 411,1 kB | .jpg | 352.778 x 239.183 mm - 1000 x 678

Pixel - 72 dpi

Dimension/Product/Basic




| 155,8 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695
Pixel - 72 dpi

| 11,7 kB | .png | 74.083 x 51.506 mm - 210 x 146
Pixel - 72 dpi

| 39,0 kB | .cdr |

Graphic/Product/Contact



| 127,2 kB | .jpg | 352.778 x 351.719 mm - 1000 x 997
Pixel - 72 dpi

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on 492021-01-30T21:19:49+01:00901Europe/BerlinSat, 30 Jan 2021 21:19:49
+010049pmSaturday.30pm31Europe/BerlinCET1901Europe/BerlinJanuary2021Sat, 30 Jan 2021 21:19:49
+010001pm31

Generated on 492021-01-30T21:19:49+01:000901Europe/BerlinSat, 30 Jan 2021 21:19:49
+010049pmSaturday.30pm31Europe/BerlinCET1901Europe/BerlinJanuary2021Sat, 30 Jan 2021 21:19:49
+010001pm31

+010049pmSaturday.30pm31Europe/BerlinCET1901Europe/BerlinJanuary2021Sat, 30 Jan 2021 21:19:49
+010001pm31

+010001pm31