



IFOD 10-30-10/01P

- DC 3-wire
- Design M30
- Metal enclosure
- Wiring compartment
- Wiring compartment can be turned 180°

Data

Ordering data

IFOD 10-30-10/01P

103038716

EAN (European Article Number)

4030661545974

General data

IEC/EN 60947-5-2

DIN VDE 0660-208

Housing construction form

Cylinder, thread

Enclosure material

Brass

Enclosure coating material

nickel-plated

Active area

Plastic

Material of the nuts

Brass

Detection range, maximum S_d

1,000 mm

Gross weight

148.2 g

General data - Features

Integral System Diagnostics, status

Yes

Number of cable wires

3

Mechanical data

Range, maximum

1 mm

Tightening torque of nuts, maximum

30 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection
	3 x 1.5 mm ²
Wire cross-section	15 AWG

Mechanical data - Dimensions

	M30
width across flats	36 BK
Height of sensor	46 mm
Length of sensor	118 mm
Width of sensor	46 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-5 °C
Ambient temperature, maximum	+70 °C
	II

Electrical data

Voltage type	DC (direct current)
Operating voltage, minimum	10 V
Operating voltage, maximum	60 V
No-load current	2.4 mA
Operating current	400 mA
Switching element	NO contact or NC contact
Protection circuit integrated	inductive interference protection
Switching frequency, approx.	100 Hz

Electrical data - Digital Output

Voltage drop U_d , maximum	2 V
Current at Voltage drop U_d	0.4 A
Versions	p-type

Status indication

Note (Integral System Diagnostics, status)	yellow LED
---	------------

Ordering code

Product type description:

IFOD (1)-(2)-(3)(4)

(1)

8 Switching distance 800 mm

10 Switching distance 1000 mm

(2)

30 Cylinder, thread M30, metal

300 Cylinder, thread M30, plastic

(3)

01 Opener (NC)

10 Normally open contact (NO)

10/01 NO contact / NC contact with wiring compartment

11 1 NO contact / 1 NC contact antivalent

(4)

without Design of control output Two-wire

P p-type

Pictures

Photo/Product/Catalogue



ID: kifo8f02

| 45,6 kB | .png | 74.083 x 111.125 mm - 210 x 315

Pixel - 72 dpi

| 518,4 kB | .jpg | 352.778 x 529.167 mm - 1000 x

1500 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 312021-01-31T16:49:31+01:000401Europe/BerlinSun, 31 Jan 2021 16:49:31

+010031pmSunday.31pm31Europe/BerlinCET4901Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:49:31

+010001pm31