


PSC1-C-100-MC



- Memory card
- 6 Signalling outputs
- 2 safety relay contacts
- 14 safe inputs on the base module
- 20 switchable, safe inputs / outputs
- Modularly expandable to up to 272 safe inputs / outputs
- Safe spindle monitoring To EN 61800-5-2 (Safe Drive Monitoring) for up to 12 spindles
- 4 safe 2 A pp-switching semiconductor outputs, switchable to 2 safe p- / n-switching semiconductor outputs

Data

Ordering data

	PSC1-C-100-MC
	103008451
EAN (European Article Number)	4030661455129
eCl@ss number, Version 9.0	27-37-18-19

Approval - Standards

TÜV
cULus
EAC

General data

Product name	PSC1
Terminal (mechanical)	Removable screw terminals
Gross weight	1,200 g

General data - Features

SD Card Slot	Yes
Number of pulse outputs (test pulse output)	6

Number of relay outputs (1-channel)	2
Number of digital fail-safe inputs	14
Number of digital fail-safe in-/outputs	20
Number of fail-safe digital outputs	4
Number of signalling outputs	6
Anzahl der Erweiterungsbaugruppen, maximal	8

Safety appraisal

Performance level, up to	e
Control category to EN13849	4
PFH-value	$1.22 \times 10^{-8} /h$
Safety Integrity Level (SIL), applicable for	3
Mission Time	20 Year(s)

Mechanical data

Mounting	can be clipped into standard rail
----------	-----------------------------------

Mechanical data - Connection technique

	0.2 mm ²
	2.5 mm ²
Wire cross-section, minimum	24 AWG
Wire cross-section, maximum	12 AWG

Mechanical data - Dimensions

Width	112.5 mm
Height	100 mm
Depth	115 mm

Ambient conditions

	IP20
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+50 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Relative humidity, minimum	5 %
Relative humidity, maximum	85 %
Note (Relative humidity)	non-condensing
Zulässige Aufstellhöhe über NN, maximum	2,000 m

Ambient conditions - Insulation value

Electrical data

Operating voltage, minimum	20.4 VDC
Operating voltage, maximum	28.8 VDC

Electrical data - Fail-safe digital outputs

Versions	short-circuit proof, p-type (Q2 und Q3)
----------	---

Electrical data - Electromagnetic compatibility (EMC)


DIN EN 62061
DIN EN 61800-3
DIN EN 61000-6-4
DIN EN 61000-6-7
DIN EN 61326-3
DIN EN 61000-6-2

Scope of delivery

Included in delivery	Backplane bus connector Connector terminals
----------------------	--

Pictures

Photo/Product/Catalogue



ID: kpsc1f06

| 51,0 kB | .png | 74.083 x 67.733 mm - 210 x 192

Pixel - 72 dpi

| 882,2 kB | .jpg | 352.778 x 322.086 mm - 1000 x 913

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 522021-01-31T12:53:52+01:001201Europe/BerlinSun, 31 Jan 2021 12:53:52

+010052pmSunday.31pm31Europe/BerlinCET5301Europe/BerlinJanuary2021Sun, 31 Jan 2021 12:53:52

+010001pm31