



IFL4-120-10

- AC 2-wire
- Design M12
- Double-insulated
- Thermoplastic enclosure

Data

Ordering data

	IFL 4-120-10
	101141523
EAN (European Article Number)	4030661122250
eCl@ss number, Version 9.0	27-27-01-01

Approval - Standards

CCC

General data

	IFL - M 12
	IEC/EN 60947-5-2
	DIN VDE 0660-208
Housing construction form	Cylinder, thread
Installation conditions (mechanical)	not flush
Enclosure material	Plastic
Active area	Plastic
Material of the nuts	Plastic
Material of the washer	Perbunan [®]
Gross weight	80 g

General data - Features

Integral System Diagnostics, status	Yes
Number of cable wires	2

Mechanical data

Switch distance	4 mm
Tightening torque of nuts, maximum	0.9 Nm

Mechanical data - Connection technique

Terminal Connector	Cable H03VV-F
Length of cable	2 m
Wire cross-section	0.5 mm ² PVC

Mechanical data - Dimensions

	M12
width across flats	17 BK
Length of sensor	71 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
	II

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Voltage type	AC (alternating current)
Rated supply frequency, minimum	45 Hz
Rated supply frequency, maximum	65 Hz
Operating voltage, minimum	15 V
Operating voltage, maximum	250 V
Operating current, minimum	8 mA
Operating current	200 mA
Switching element	Normally open contact (NO)
Protection circuit integrated	inductive interference protection
Switching frequency, approx.	10 Hz

Electrical data - Digital Output

Voltage drop U_d , maximum	3.5 V
Current at Voltage drop U_d	0.2 A
Versions	Two-wire

Status indication

Note (Integral System Diagnostics, status) yellow LED

Ordering code

Product type description:

IFL (1)-(2)(3)-(4)(5)(6)(7)(8)-(9)

(1)

2 Switching distance 2 mm

4 Switching distance 4 mm

NB, MBN, BN Quasi-embeddable

(2)

12 Cylinder, thread M12, metal

120 Cylinder, thread M12, plastic

(3)

without Standard body

M Miniature body

L Long design

(4)

01 Opener (NC)

10 Normally open contact (NO)

10/01 NO contact / NC contact with wiring compartment

11 1 NO contact / 1 NC contact antivalent

(5)

without Cable

ST Male connector

T Conductor with strain relief

(6)

without Standard connector version

2 Alternative connector
version

(7)

N n-type

P p-type

(8)

1 pulsed

2033 Stainless steel enclosure

Photo/Product/Catalogue



| 17,7 kB | .png | 74.083 x 111.125 mm - 210 x 315
Pixel - 72 dpi

| 223,8 kB | .jpg | 352.778 x 529.167 mm - 1000 x
1500 Pixel - 72 dpi

[illegible]

| 23,6 kB | .cdr |
| 3,3 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi
| 74,7 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

| 29,6 kB | .cdr |
| 39,3 kB | .jpg | 352.778 x 148.167 mm - 1000 x 420
Pixel - 72 dpi

+010001pm31